

SCHMIDT[®] Presses Simply the best!













Table of Contents



Introduction

ManualPress	II
 Rack-and-Pinion Presses Toggle Presses NockenPresse 11N DuplexPress 8 ManualPress 305, 307, 311 with Process Monitoring 	02 04 10 12 16
Hydro-/Pneumatic Presses	III
 PneumaticPress Direct Acting Presses PneumaticPress Toggle Presses PneumaticPress Force/Stroke Monitoring HydroPneumaticPress C-Frame Design HydroPneumaticPress Force/Stroke Monitor. HydroPneumaticPress H-Frame Design Cylinder Units 	04 08 12 18 22 26 28
Electric Presses	IV
 ElectricPress ServoPress TorquePress 	01 06 10
Control Units	V
 PressControl 75 PressControl 700 PressControl 7000 Visualization & Process Analysis Software Tools, PRC DataBase PRC FileXchange PRC DataXchange PRC OpenFieldBus, PRC OPC Hardware Tools 	02 03 04 06 07 08 09 09 09 10
Safety Concepts, Single Workstations	VI
 Single Workstations SmartGate SmartGuard Classic Safety Concepts Press Bases, Four-column Gantry Slide Tables Customer-Specific Solutions 	01 02 03 04 05 06 07

SupportServiceService

Family-Run Company As internationally accepted Technology Leader



SCHMIDT Technology is a family-run, medium-sized enterprise at the highest technological level. The success speaks for itself: Today, products and services from SCHMIDT Technology are exported to over 80 countries of the world.

The safety and quality of SCHMIDT Technology products make them unique on the global market and thus sought after for decades. The international orientation of the company and the combination of creative and intelligent solutions, together with economic and efficient manufacturing in Germany, lay the groundwork for the successful future-oriented position of the enterprise.

Because of this, SCHMIDT Technology is valued internationally as a solid, dependable and competent partner. The outstanding characteristics of a successful company must include a strong visionary innovation potential.

SCHMIDT Technology recognized this at an early stage and invested ardently in the fields of research and development. At the same time, the company traditionally keeps in close contact with external research institutes and universities.

As a result, the name SCHMIDT Technology is associated with highest quality standards worldwide. In keeping with this, SCHMIDT Technology holds all relevant quality certificates such as DIN EN ISO 9001.



Your profitability Is our top priority

The task to assemble two or more components requires a careful decision about the joining method.

Traditional processes such as bolting, soldering, welding or glueing are continuously being replaced with cost effective and efficient pressing operations.

These are exactly our strengths.



Use our knowledge for your application

The right press type can be chosen depending on the application. Today, **SCHMIDT® Presses** stand for first-class assembly technology worldwide. This applies both for stand-alone machines and for assembly modules integrated in complex automation lines.

SCHMIDT Technology a leader in intelligent joining technology, has the widest product range of all producers. From SCHMIDT® ServoPress and SCHMIDT® HydroPneumaticPress or SCHMIDT® PneumaticPress and SCHMIDT® ElectricPress up to our SCHMIDT® ManualPress range, our solutions are tailored to meet all of your process requirements. Apart from the presses, the safety and control technology of the SCHMIDT® PressesControl sets standards due to its system philosophy, force/stroke monitoring and integrated measurement technology. A continuous process control and the essential ISO-conforming documentation are the tools for high productivity in today's efficient assembly. These performance features make SCHMIDT Technology the undisputed technological leader in the field of precision joining technology today.

This is the basis for the excellent reputation of **SCHMIDT Technology**, specifically in the key sectors such as automobile technology, aerospace technology, electrics/electronics, micromechanics and medical technology.







Snap Fitting



Forming Calibrating / Sizing



Crimping

Forming



Riveting



Marking



Bending



Punching



Cutting



Joining

In Partnership To success

A global market requires linked processes. Thanks to the OPC connection via Ethernet technology, you can access your process data at any time. Furthermore, local representation and rapid response are essential. Our worldwide distribution network of subsidiaries and trained sales & support partners ensure that our customers will receive full support for all their requirements. All our representatives' support teams have been trained specifically on our products.

Deciding in favour of our technology is the first step to a successful partnership.

The economic success is then shown in daily production. High quality products optimized for assembly processes are as important as an efficient after-sales service. Our name is your guarantee.



Skills to your advantage

All our training centers provide machinery and full expertise to assist our customers with their applications.

On this basis, a team of skilled engineers plan economic solutions from the simple manual workstation to the fully automated assembly line.

Competent technical customer service is our strength. We offer training courses and seminars in our **SCHMIDT® TrainingCenters**. Your employees will achieve sustainable knowledge of the presses and their practical use resulting in a benefit for your products.



Safety without compromise

In 2006, the EC Machine Directives became national law in the EU member states. The articles of this agreement were the determining factors for the design of safety controls for assembly and press technology. Furthermore, a EC type approval became necessary for applications with manual workstations.

Even before the most recent regulations became legally binding, **SCHMIDT Technology** had delivered all press systems in compliance with this new law to all its customers (even to countries where these regulations are not implemented).

Our philosophy does not allow making compromises with regard to safety and health of the user.





SCHMIDT[®] ManualPress From 1.6 kN to 22 kN

Efficient manufacturing requires appropriate means of production – not always automation. In particular, with small production runs, manual presses are often the most cost effective solutions.

We are continually developing the range of manual presses so that you can achieve your production targets. The expertise we have gained from our exposure to numerous production applications has been implemented in our new models. Therefore, we can offer a wide range of manual presses to suit all requirements.

Characteristics

- Flexibility
 - Rapid changeover due to the easy and secure adjustment of the working height
 - Table tops with precision T-slot and precise alignment between the ram and table bores allow for accurate and repeatable set ups which reduces set-up times
 - The original position of the hand lever can be varied by 360°
 - Horizontal pull (111/113)
 - Available for left-handed and right-handed use
 - The return stroke force of the ram can be adapted to different tool weights
- Precision
 - Alignment < 0.05 mm between upper and lower tool
- Maintenance-free
- No lubrication necessary
- Long service life

Depending on the application, there is a wide selection of rackand-pinion presses and toggle presses to choose from. Furthermore, a modular product design gives you the opportunity to choose the appropriate press for your application.



SCHMIDT® Rack-and-Pinion Presses Constant force over the entire stroke

Do you need force over a longer stroke distance for assembly processes? Then SCHMIDT® Rack-and-Pinion Presses are the right choice.

Characteristics

- Long stroke
- Linear force progression
- Precise adjustment of the press depth via an integrated hardened adjustable stop
- Honed ram guiding and ground rams provide a long service life and a precise guidance



Press Type 5



Improved return stroke mechanism for rack-andpinion presses No. 3 and 6 with stroke 100 mm and 160 mm

The use of a spring package optimized specifically for large strokes improves ergonomics significantly. In addition, the use of the Ergohandle ensures that even with angles of rotation >360°, no switching of hand position is necessary. The force feedback on the hand lever is kept as constant as possible over the entire stroke by a balance weight.



Press Head

No.1 and No.2 have a ground guidance plate and teflon-coated adjustable gibs for precise and torsion-proof guidance.



Press Type 3 or 6

110

|| 02 | SCHMIDT[®] Presses



From 1.6 kN to 2.5 kN

Press Type			5	5R	3	ЗR	6	6R	1	1R	2	2R
Press head type			5	5R	3	ЗR	3	ЗR	1	1R	1	1R
Nominal force		kN	1.6	1.6	2.4	2.4	2.4	2.4	2.5	2.5	2.5	2.5
Working stroke up to	Α	mm	40	40	70	70	70	70	80	80	80	80
					160	100	160	100	100	100	100	100
Press head height	S	mm	240	240	350	350	350	350	400	400	400	400
					350	350	350	350				
Throat depth	С	mm	65	65	86	86	86	86	86	86	86	86
Ram bore	Ø	mm	10H7	10H7	10H7	10H7	10H7	10H7				
Collet (standard Ø10)	Ø	mm							1-17	1-17	1-17	1-17
Hand lever left			0	0	0	0	0	0	•	•	•	•
Angle of rotation/mm strol	ke		4.1°	4.1°	3.2°	3.2°	3.2°	3.2°	2.2°	2.2°	2.2°	2.2°
Max. weight of the upper tool 2)		kg	1.5	1.0	2.5	2.0	2.5	2.0	1.0	1.0	1.0	1.0
Return stroke lock 1)												
Minimum working stroke	<u>e</u>	mm		17		18		18		26		26
Locked position 1	mm l	oef. BDC		11.5		13		13		19.5		19.5
Locked position 2	mm l	oef. BDC		3.5		4.5		4.5		7		7
Disengaging accuracy		mm		0.06		0.07		0.07		0.08		0.08
Working height ³⁾	F											
Frame No. 13		mm	55-200	55-200								
Frame No. 3		mm			75-220	75-220			120-260	120-260		
Frame No. 2		mm					100-355	100-355			145-360	145-360
Frame No. 2-600 O		mm			200-600	200-600	200-600	200-600	245-650	245-650	245-650	245-650
Frame No. 2-1000 o		mm			330-1030	330-1030	330-1030	330-1030	380-1080	380-1080	380-1080	380-1080
Weight	арри	ox. kg	11	11	22	22	30	30	23	23	31	31
Accessories			5	5R	3	3R	6	6R	1	1R	2	2R
Mechanical counter			0	0	0	0	0	0	0	0	0	0
Throat depth frame (total 111 mm, 131 mm, 160 m	l deptł m, 200	n) D mm			0	0	0	0	0	0	0	0
Additional fixture mount suitable for throat depth	ing pla frame	ate ?			0	0	0	0	0	0	0	0
Micrometer stop			0	0	0	0	0	0				
			Dress T		Frame Hei	ght M	Table Size	Tabl	e Bore	Table Heig	ht Mount	ing Surface

Frame Overview	Press Type	Frame Height M without height adj. (mm)	B x T (mm)	D (Ø mm)	K (mm)	B x L (mm)
No. 13	5	330	110 x 80	20H7	46	110 x 185
No. 3	3, 1	400	150 x 110	20H7	60	150 x 260
No. 2	6, 2	536	185 x 110	20H7	60	185 x 280
No. 2-600	3, 6, 1, 2	810	200 x 160	20H7	98	200 x 290
No. 2-1000	3, 6, 1, 2	1250	200 x 160	20H7	98	200 x 290

Options

- Series with no additional charge o Additional charge applies
- ¹⁾ Adjustment of locking position on request
- ²⁾ The weight was determined with hand lever position 45° forward (guide)
- ³⁾ Typical values; can vary ± 3 mm due to casting and production tolerances

Other available options

- Nickel plated cast parts are electroless nickel plated, steel components black oxide finished, aluminum anodized, precision steel surfaces are untreated
- Custom paint press and column can be painted to customer's color specification
- Bores for adapting tooling customer specific sizes can be supplied





Detailed dimensional drawings can be downloaded: www.schmidttechnology.de

SCHMIDT[®] Toggle Presses The high force at the end of stroke, just where it is important

Do you need a high force at the end of stroke for material transforming processes? Then **SCHMIDT®** Toggle Presses are just the right choice.

Characteristics

- High force at the end of stroke (see diagramm below)
- Honed bores and ground rams provide a long service life and a precise guidance



Press Type 13RFZ

Press Type 11 / 14 - 17



Maximum force will be reached just before extended position



From 5 kN to 15 kN

Press Type			13 125	13R	11	11R	15 155	15R	14	14R	16 165	16R	17
			13-40	13R-/10	11-45	11R-45	11R-45	11R-45	11-60	11R-60	11-60	11R-60	11_20
Press head type			13F-35	13RF-35	11F-35	11RF-35	11F-35	11RF-35	11F-50	11RF-50	11F-50	11RF-50	11F-20
Nominal force		kN	5	5	12	12	12	12	12	12	12	12	15
Working stroke up to	Α	mm	40	40	45	45	45	45	60	60	60	60	20
Threat depth	~		35 CE	35 CE	35	35 -7	35 "	35 -7	50	50	50	50	20 - 37
inroat depth	Ľ	mm	205	205	520	520	520	520	500	500	500	500	620
Press head height	S	mm	400	400	540	540	540	540	520	520	520	520	640
Ram bore	Ø	mm	10H7	10H7	10H7	10H7	10H7	10H7	10H7	10H7	10H7	10H7	10H7
Hand lever left			0		0		0		0		0		
Angle of rotation			95°	95°	110°	110°	110°	110°	125°	125°	125°	125°	90°
Max. weight upper tool	3)	ka	1.2/3.5	1.2/3.5	2/4.5	2/4	2/4.5	2/4	1.5/2.5	1.5/2.5	1.5/2.5	1.5/2.5	2.5/-
standard / reinforced spi	ring	ĸġ	1.5/3	1.5/3	2.5/6	2/6	2.5/6	2/6	2/5	1.5/4	2/5	1.5/4	2.5/-
Return stroke lock 1)													
Minimum working stroke		mm		25		20		20		24		24	
Locked position 1	mm l	oef.DC		13.5		12		12		14		14	
Locked position 2	mm l	oef.DC		1.5		1.5		1.5		1.5		1.5	
Disengaging accuracy		mm		0.03		0.03		0.03		0.04		0.04	
Working height 4)	F												
Frame No. 13		mm	65 - 180 40 - 155	65 - 180 40 - 155									
Frame No. 3		mm			75-210 50-185	75-210 50-185			90-220 65-195	90-220 65-195			65-200 50-185
Frame No. 5													65-315 50-300
Frame No. 2		mm					100-345 80-325	100-345 80-325			110-360 85 - 335	110-365 85-335	
Frame No. 2-600 O		mm			200-585 175-560	200-585 175-560	200-585 175-560	200-585 175-560	210-595 185-570	210-595 185-570	210-595 185-570	210-595 185-570	190 - 575 175-560
Frame No. 2-1000 0		mm			330-1020	330-1020	330-1020	330-1020	340-1030	340-1030	340-1030	340-1030	315-1015
			4.5	4.5	305-1000	305-1000	305-1000	305-1000	315-1010	315-1010	315-1010	315-1010	300-1000
vveight	appro	ox. kg	12	12	23	24	29	29	24	24	29	29	23
Accessories			13 13F	13R 13RF	11 11F	11R 11RF	15 15F	15R 15RF	14 14F	14R 14RF	16 16F	16R 16RF	17 17F
Mechanical counter			0	0	0	0	0	0	0	0	0	0	0
Throat depth frame (tota 111 mm, 131 mm	al dep	oth)			0	0	0	0	0	0	0	0	
Additional fixture moun suitable for throat depth	ting p n fram	late ie			•	•	•	•	•	•	•	•	•
Block clamping piece ²⁾			0 0	0 0	•	•	•	•	0 0	0	0	0	•
Frame Overview		Pres	ss Type	Fram M	e Height (mm)	Tab B x ⁻	le Size T (mm)	Tabl	e Bore 0 mm)	Table K (Height mm)	Mountin B x L	g Surface (mm)

Frame Overview	Press Type	M (mm)	B x T (mm)	D (Ø mm)	K (mm)	B x L (mm)
No. 13	13	475	110 x 80	20H7	46	110 x 185
No. 3	11, 14, 17	540	150 x 110	20H7	60	150 x 260
No. 5	17	536	185 x 110	20H7	60	185 x 275
No. 2	15, 16	700	185 x 110	20H7	60	185 x 280
No. 2-600	11, 14, 15, 16, 17	974	200 x 160	20H7	98	200 x 290
No. 2-1000	11, 14, 15, 16, 17	1410	200 x 160	20H7	98	200 x 290

Options

• Series with no additional charge • Additional charge applies

¹⁾ Adjustment of locking position on request

- ²⁾ Stroke reduction about 10 mm by version with additional charge
- ³⁾ The weight was determined with hand lever position 45° forward (guide)
- ⁴⁾ Typical values; can vary ± 3 mm due to casting and production tolerances
- $^{\scriptscriptstyle 5)}$ Stroke adjustable with stop clamp (in the scope of delivery)

Other available Options

- Nickel plated cast parts are electroless nickel plated, steel components black oxide finished, aluminum anodized, precision steel surfaces are untreated
- Custom paint press and column can be painted to customer's color specification
- Bores for adapting tooling customer specific sizes can be supplied



Detailed dimensional drawings can be downloaded: www.schmidttechnology.de

L

SCHMIDT[®] Toggle Presses with Horizontal Pull The high force at the end of stroke, just where it is important

Do you need a high force at the end of stroke for material transforming processes? Then **SCHMIDT**[®] **Toggle Presses** are just the right choice.

Characteristics

- High force at the end of stroke (see diagramm below)
- Honed bores and ground rams provide a long service life and a precise guidance



Press Type 113RFZ



Ergonomic Press with horizontal pull

With press No. 113 and No. 111 the manual force is applied by pulling the lever towards the body. This press is especially suitable for rapid production at small forces. We supply press No. 111 including the ergonomic handle (standard scope of supply).



Maximum force will be reached just before extended position



From 2.5 kN to 12 kN

Press Type			113 113F	113R 113RF	111 111F	111R 111RF
Press head type			113 113F	113R 113RF	111 - 45 111F - 50	111R - 45 111RF - 50
Nominal force		kN	2.5	2.5	12	12
Working stroke up to ⁵⁾	Α	mm	28 28	28 28	45 50	45 50
Throat depth	С	mm	65	65	86	86
Press head height	S	mm	170 180	190 200	215 225	240 250
Ram bore	Ø	mm	10H7	10H7	10H7	10H7
Hand lever left			-	-	-	-
Angle of rotation			80°	80°	90°	90°
Max. weight upper tool ³⁾ standard / reinforced spring		kg	1/3 0.6/3	0.5/2.5 0.6/3	2.5/- 3/-	2.5/- 3/-
Return stroke lock 1)						
Minimum working stroke		mm		22		24
Locked position 1	mm b	ef. BDC		12		14
Locked position 2	mm b	ef. BDC		0.5		1.5
Disengaging accuracy		mm		0.03		0.07
Working height ⁴⁾	F					
Frame No. 13		mm	50 - 165 40 - 155	50 - 165 40 - 155		
Frame No. 3		mm			120 - 205 105 - 195	120-205 105-195
Frame No. 2		mm			120-345 105-335	120-345 105-335
Frame No. 2-600 O		mm			200-580 185-570	200 - 580 185 - 570
Frame No. 2-1000 O		mm			330-1020 310-1000	330-1020 310-1000
Weight	арр	rox. kg	11	11	28	28

Accessories	113 113F	113R 113RF	111 111F	111R 111RF
Mechanical counter	0	0	0	0
Throat depth frame (total depth) 111 mm, 131 mm			0	0
Additional fixture mounting plate suitable for throat depth frame			0	0
Block clamping piece ²⁾	•	•	•	•

Frame Overview	Press Type	Frame Height M (mm)	Table Size B x T (mm)	Table Bore D (Ø mm)	Table Height K (mm)	Mounting Surface B x L (mm)
No. 13	113	475	110 x 80	20H7	46	110 x 185
No. 3	111	540	150 x 110	20H7	60	150 x 260
No. 2	111	700	185 x 110	20H7	60	185 x 280
No. 2-600	111	974	200 x 160	20H7	98	200 x 290
No. 2-1000	111	1410	200 x 160	20H7	98	200 x 290

-

L

Options

- Series with no additional charge Additional charge applies
- ¹⁾ Adjustment of locking position on request
- ²⁾ Stroke reduction about 10 mm by version with additional charge
- ³⁾ The weight was determined with hand lever position 45° back (guide)
- ⁴⁾ Typical values; can vary ± 3 mm due to casting and production tolerances
- $^{\scriptscriptstyle 5)}$ Stroke adjustable with stop clamp (in the scope of delivery)

Other available options

- Nickel plated cast parts are electroless nickel plated, steel components black oxide finished, aluminum anodized, precision steel surfaces are untreated
- Custom Paint Press and column can be painted to customer's color specification
- Bores for adapting tooling customer specific sizes



Detailed dimensional drawings can be downloaded: www.schmidttechnology.de

SCHMIDT® Toggle Presses with Square Ram Optimum guidance and anti-rotation

Do you need a high force at the end of stroke for materialtransforming processes? Then SCHMIDT® Toggle Presses are just the right choice.

Characteristics

- High force at the end of stroke
- Square ram is anti-rotational (no die sets required)
- Fully adjustable, play-free teflon-lined gibs



2 = No. 19 force at the hand lever 120 N

Maximum force will be reached just before extended position

No. 13 see on page 8



From 5 kN to 22 kN

Press Type			13 V 13 VF	13 VR 13 VRF	11 V 11 VF	15 V 15 VF	11 VR 11 VRF	15 VR 15 VRF	14 V 14 VF	16 V 16 VF	14 VR 14 VRF	16 VR 16 VRF	19 V 19 VF	19 VR 19 VRF
Press head type			13V-40 13VF-40	13VR-40 13VRF-40	11V-45 11VF-45	11V-45 11VF-45	11VR-45 11VRF-45	11VR-45 11VF-45	11V-60 11VF-60	11V-60 11VF-60	11VR-60 11VRF-60	11VR-60 11VRF-60	19V-40 ¹⁾	19VR-401)
Nominal force		kN	5	5	12	12	12	12	12	12	12	12	22	22
Working stroke up to 5	Α	mm	40	40	45	45	45	45	60	60	60	60	40	40
Throat donth	C	mm	40	40	45	45	45	45	60	60	60	60	40	40
initial depth	C		205	205	E10	50 E10	E10	E10	E10	50 E10	E10	50 E10	620	620
Press head height	S	mm	400	400	530	530	530	530	530	530	530	530	620	620
Ram bore	Ø	mm	10H7	10H7	10H7	10H7	10H7	10H7	10H7	10H7	10H7	10H7	20H7	20H7
Hand lever left			0		0	0			0	0			•	•
Angle of rotation			95°	95°	110°	110°	110°	110°	125°	125°	125°	125°	175°	175°
Max weight upper too	.[3)		12/4	12/4	16/42	16/42	16/42	16/42	1/3 5	1/3 5	1/3 5	1/3 5	2/-	2/-
standard / reinforced st	orina	kg	2/35	2/35	2/5	2/5	2/5	2/5	1/3 5	1/3.5	1/3 5	1/3 5	2/-	2/-
Return stroke lock 2)	J		275.5	275.5	275	275	275	275	175.5	175.5	17 3.5	175.5	27-	27-
Minimum working stro	ke	mm		26			20	20			28	28		10
Locked position 1	mm	bef. BDC		14.5			12	12			14	14		4.5
Locked position 2	mm	bef. BDC		15			1.5	1.5			15	15		0.9
Disengaging accuracy		mm		0.03			0.03	0.03			0.04	0.04		0.02
Working height 4)	F													
			65-180	65-180										
Frame No. 13		mm	50-165	50-165										
Furner Ne. 2					80-210		80-210		80-210		80-210			
Frame No. 3		mm			60-190		60-190		60-190		60-190			
Frame No. 2		mm				105-350		105-350		105-350		105-350		
						85-330		85-330		85-330		85-330		
Frame No. 2-600 o		mm				200-585		200-585		210-590		210-590		
						185-5/0		185 - 570		195-5/5		195 - 575		
Frame No. 2-1000 o		mm				330-1020 315-1000		330-1020		340-1030 325-1015		340-1030 325-1015		
Frame No. 19		mm				010 1000		0.00		020 1010		020 1010	90-220	90-220
Frame No. 19-400 o		mm											160-400	160-400
Frame No. 19-500 O		mm											260-550	260-550
Weight	appro	ox. kg	12	12	24	32	24	32	24	32	24	32	85	85
Accessories			13 V	13 VR	11 V	15 V	11 VR	15 VR	14 V	16 V	14 VR	16 VR	19 V	19 VR
Accessories			13 VF	13 VRF	11 VF	15 VF	11 VRF	15 VRF	14 VF	16 VF	14 VRF	16 VRF	19 VF	19 VRF
Mechanical counter			0	0	0	0	0	0	0	0	0	0	0	0
Throat depth frame 11' 131 mm	l mm,				0	0	0	0	0	0	0			
Throat depth frame 15	1 mm												0	0
Additional fixture mou	ntina	plate				_	_	_	_		_	_	_	_
suitable for throat dept	h frar	ne			0	0	0	0	0	0	0	0	0	0
Frame Overview			Press	Туре	Frame M (I	Height mm)	Tabl e B x T	e Size (mm)	Table D (Ø	e Bore mm)	Table K (r	Height nm)	Mountin B x L	g Surface (mm)
No. 13			1	3	4	75	110	x 80	20	H7	4	-6	110	x 85
No. 3			11,	14	54	40	150	x 110	20	H7	6	0	150 >	x 260
No. 2			15,	16	7	00	185	x 110	20	H7	6	0	185 >	x 280
No. 2-600 o			15,	16	9	74	200	x 160	20	H7	9	8	200>	x 290
No. 2-1000 O			15,	16	14	10	200	x 160	20	H7	9	8	200>	x 290
No. 19			1	9	64	40	200	x 160	25	H7	1	12	200 x 370	
No. 19-400 O			1	9	84	40	250	x 200	40	H7	14	45	250 >	x 460
No. 19-500 o			1	9	10	00	250	x 200	40	H7	14	45	250 >	x 480

Options

Series with no additional charge o Additional charge applies
 ¹⁾ Special strokes 12 mm and 50 mm on request
 ²⁾ Adjustment of locking position on request

- ³⁾ The weight was determined with hand lever position 45° forward (guide)
- ⁴⁾ Typical values; can vary \pm 3 mm due to casting and production tolerances ⁵⁾ Stroke adjustable with stop clamp (in the scope of delivery)
- ⁵⁾ Adjustable stroke

Other available options

- Nickel plated cast parts are electroless nickel plated, steel components black oxide finished, aluminum anodized, precision steel surfaces are untreated
- Custom Paint Press and column can be painted to customer's color specification
- Bores for adapting tooling customer specific sizes



Detailed dimensional drawings can be downloaded: www.schmidttechnology.de

SCHMIDT® CamPress 11N The best of both worlds

We have merged the best features of the two hand lever press types, the toggle press and the rack and pinion press, and combined them in the **SCHMIDT**[®] **CamPress 11N**. Thanks to this clever mechanism, the patented assembly press is characterized by a particularly smooth operation and strong force at the end of the stroke. The sophisticated mechanics make the manual CamPress 11N particularly ergonomic and user-friendly. This unique motion creates a high, linear force progression with high breakaway torque at the beginning of the ram movement and a steep force increase at the end of the stroke; and all this with constant hand force.

The use of the balance weights and the ErgoHandle ensures a smooth motion process and-ergonomic operation of the hand lever. Both components and height adjustment with the crank lever are part of the standard scope of delivery. Of course, the proven options such as return stroke lock, fine adjustment and mechanical counter can also be used here.





SCHMIDT[®] CamPress 11N

Examples of process-safe workstations

Press Typ			11N 11NF
Press head type			11N-23 11NF-23
Nominal force		kN	20
Working stroke up to	Α	mm	23 23
Throat	С	mm	86
Head height	s	mm	458 481
Ram bore	Ø	mm	10H7
Hand level left			
Rotation angle / stroke		0	180
Max. weight upper tool 3)		kg	2
Return stroke lock ²⁾			
Minimum working strol	ke	mm	10.3
Locked position 1	mm t	oef. BDC	12.7
Locked position 2	mm Ł	ef. BDC	1.8
Disengaging accuracy		mm	0.05
Working height ⁴⁾	F		
Frame No 5		mm	75 – 320 55 – 300
Weight		~ kg	40
Option			11N 11NF
Mechanical counter			0



CamPress 11N in comparison to Toggle Press and Rack and Pinion Press

Frame	Press Typ	Frame height M (mm)	Table size B x T (mm)	Table bore D (Ø mm)	Table height K (mm)	Footprint B x L (mm)
No. 5	11N	587	185 x 110	20 ^{H7}	60	185 x 273

Options

- Series with no additional charge Additional charge applies
- ²⁾ Adjustment of locking position on request
- ³⁾ The weight was determined with hand lever position 45° forward (guide)
- ⁴⁾ Typical values; can vary ± 3 mm due to casting and production tolerances

Other available options

- Nickel plated cast parts are electroless nickel plated, steel components black oxide finished, aluminum anodized, precision steel surfaces are untreated
- Custom paint press and column can be painted to customer's color specification
- Bores for adapting tooling customer specific sizes



Patented mechanics with high force at the end of the stroke





SCHMIDT® DuplexPress 8 With minimal effort of 0,12 kN a high force of 7 kN

The **SCHMIDT**[®] DuplexPress 8 breaks new ground for familiar hand lever presses with a completely new operating principle. The challenge of achieving high forces (7 kN) with long strokes (up to 140 mm) is not possible either with conventional rack and pinion or toggle presses. Thus this new developed press represents a very universal solution for pressing tasks, which can also be used extremely ergonomically with low hand force (120 N).

SCHMIDT'

The left hand lever actuates the approach stroke to position the ram quickly to the workpiece.

The right hand crank activates the power stroke any time with little manual force. The transmission ratio of the planetary gearbox achieves a high effective force on the ram. This is useful, for example, when a long stroke has to be covered before reaching the component where the high forces of the press are required.

Why compressed air?

Why does the press have a compressed air connection or an accumulator?

The compressed air retracts the ram back to the TDC (top dead center) with constant force and speed. In addition, the speed can be individually adjusted with the pressure regulator, this pneumatic driven return stroke increases the ergonomic compared to a conventional spring solution. In addition, the two-chamber design of the tank ensures that the weight of the upper tool can be compensated via the adjustable differential pressure.

The version with pressure tank is available for self-sufficient and maximum energy-efficient operation of the press. Thanks to the intelligent re-storage of compressed air, the loss of compressed air is minimised and it is sufficient to fill the tank about once a week. Alternatively, the press can also be connected directly to the compressed air supply.



DuplexPress in comparison to Toggle Press, Rack and Pinion Press or CamPress $11\mathrm{N}$



SCHMIDT[®] **DuplexPress 8** A long stroke of 140 mm and super ergonomic operation

Press Typ			8
Nominal force		kN	7
Working stroke	А	mm	140
Throat	С	mm	86
Head height	S	mm	446
Ram bore	Ø	mm	10 ^{H7}
Max. force at crank (power stroke)		Ν	120
Max. weight upper tool ³⁾		kg	5
Working height 4)	F	mm	35 – 285
Height adjustment			series
Head weight 8RDS		approx.kg	19.5
Mechanical counter			series
Return stroke lock for 8R, 8RD, 8RS, 8RI	OS ²⁾		
Minimum working stroke		mm	120.4
Locked position 1 (bef. BDC)		mm	19.6
Locked position 2 (bef. BDC)		mm	6.8
Disengaging accuracy		mm	± 0.04
Max. operating pressure			
Network operation		bar	6
Storage module (self-sufficient operation)		bar	8
Frame Frame beinht Table size Te	hla b	ave Teble	holeht I

Frame	Frame height	lable size	lable bore	lable height	Footprint	Weight
	M (mm)	B x T (mm)	D (Ø mm)	K (mm)	B x L (mm)	kg
No. 5	536	110 x 80	20 ^{H7}	60	110 x 185	26
No. 2-600	974	200 x 160	20 ^{H7}	98	200 x 290	52

²⁾ Adjustment of locking position on request

⁴⁾ Typical values; can vary \pm 3 mm due to casting and production tolerances

Other available options

Custom paint – press and column can be painted to customer's color specification

DuplexPress 8

Bores for adapting tooling – customer specific sizes



DuplexPress 8 R (S)



DuplexPress 8D(S)



DuplexPress 8 RD (S)

Nomenclature R = Return stroke

- lock D = Duplex (rapid approach stroke) = Storage module S
- (self-sufficient operation)



DuplexPress 8S





Volume dimensions with frame no. 5

SCHMIDT® ManualPress

Options suitable for your application



The return stroke lock guarantees reaching the required pressing depth with every stroke

- 1 TDC (Top Dead Center) position
- 2 First locking position: Loose tools can still be aligned
- **3** Second locking position before BDC (Bottom Dead Center). From here you can only continue to BDC.

4 After reaching BDC (Bottom Dead Center) and completing the stroke the return stroke lock is released. This guarantees a repeatable BDC and thus a constant press depth

5 The emergency button releases the locking function in any position



Fine adjustment with micrometer scale serves as stop for the rack and pinion presses

An optional micrometer adjustable stop developed specifically for applications that need fine adjustment of the BDC. The robust and precise design ensures the repeatability of the stop, no matter how many strokes are taken.



Fine adjustment with micrometer scale for toggle presses By loosening the set screw 1 and turning the adjusting nut 2 with the same tool, the setting of the BDC can be adjusted infinitely. The adjustment in a range of $\frac{1}{100}$ of a mm is reached rapidly and precisely.



SCHMIDT® ManualPress Options suitable for your application



Mechanical counter

A four digit counter monitors the number of pieces produced. The counter is provided with a reset function.



Collet

For the rack-and-pinion presses No. 1 and No. 2, collet bore diameter of 1 to 17 mm.



Throat extension block We offer various sizes for extended throat depths.



Special fixture mounting plates Special fixture tabletops, designed in conjunction with throat extension blocks, provide ram to table bore alignment when spacer is used.



Ergonomic left-handed design With most press types, lefthanded or left-/right-handed design is an available option.



Upper tooling adapter Adapter for tools with a diameter of 5 - 20 mm.



Nickel plated design

Press frames and cast parts are electroless nickel-plated, steel components are black oxide finished, aluminum parts are anodized, precision steel surfaces are untreated.



Ergonomic handle Swivelling handle for improved

Swivelling handle for improved comfort; easy and flexible assembly on the hand lever.



Press base Plastic (250 x 340 mm), including fasteners.



Stop clamp For Toggle Presses.

How to order

- Order key for press options
- R = incl. return stroke lock with emergency release
- F = incl. fine adjustment with micrometer scale
- Z = incl. mechanical counter
- RF= incl. return stroke lock with emergency release and fine adjustment

Order example

No. 3 R = SCHMIDT® Rack-and-Pinion Press No. 3

or

incl. return stroke lock with emergency release

No. 13 RFZ = SCHMIDT® Toggle Press No. 13

incl. return stroke lock with emergency release, fine adjustment and mechanical counter

SCHMIDT® ManualPress 300 Series Manual Presses with Process Monitoring

Process reliability, force/stroke monitoring of the joining process and EN ISO-compatible documentation of the results are becoming the major factors for small and medium production within the manual workplace.

The SCHMIDT[®] ManualPress 300 Series system with SCHMIDT[®] PressControl 700 includes:

- Integrated reliable measuring technology
- High resolution of the obtained process data
- Graphical and numerical output of the processing results
- Quality monitoring using freely selectable tolerances



Assembly system with patented return stroke lock and progammable clutch.

Process reliability - not just a slogan

The system software allows easy setup of quality control criterea for 100 % in-process monitoring.





SCHMIDT[®] ManualPress 300 Series

Process reliability for manual workplaces, force range 0.4 kN to 12 kN

Characteristics

- Linear force progression for No. 305 and No. 307
- High force at the end of stroke for No. 311
- Precise adjustment of the press depth via micrometer fine adjustment
- Guides require little maintenance, have little wear and are locked against rotation. This results in precise working and a long service life
- Optimum guidance and clamping due to dovetail guide on the press head
- Quick set-up
 - Exact alignment of ram bore to the table within 0.05 mm
 - Height adjustment using a crank
 - Precision bores in ram and column base plate

Functional components

- Electronic stroke lock
- Integrated transducer
- Force sensor
- Incremental encoder
- Integrated signal amplifier
- Programmable overload coupling





ManualPress 311



Maximum force will be reached just before extended position

No. 307	No. 311
<u> </u>	

Press Type			305	307	311
Nominal force		kN	0.4	4	12
force at the hand lever	app	prox. N	50	200	200
Working stroke up to	Α	mm	42 5)	54 ⁵⁾	50
Throat depth	С	mm	129	129	129
Press head height	S	mm	310	417	555
Ram bore	Ø	mm	6H7	10H7	10H7
Stroke fine adjustment		mm	0.02	0.02	0.02
Stroke resolution		mm	0.005	0.005	0.005
Angle of rotation/mm stroke			3.3°	4.8°	non linear
Resolution, process data acquisition	stroke force	µm/inc N/inc	5 0.125	5 1.25	5 3.5
Working height4)	F				
Frame No. 7-420		mm	60-420	50-410	50-290
Frame No. 7-600 ²⁾		mm	90-600	80-600	80-480
Max. weight upper tool ³⁾		kg	0.6	1	1.3
Weight	appro	ox. kg	41	41	60
Protection type			IP 54	IP 54	IP 54
Accessories					
Stronger return assist s	pring		0	0	
Speed control			0	0	
Throat depth frame ¹⁾ (t 169, 209, 249 mm	otal d	epth)	0	0	

Frame Overview	Press Type	Frame Height M (mm)	Table Size B x T (mm)	Table bore DØmm	Table Height K (mm)	Mounting Surface BxL(mm)
No. 7 - 420	305, 307, 311	740	180 x 150	20H7	90	220 x 362
No. 7-600 o	305 307 311	960	180 v 280	2047	110	220 x 465

Options

- Additional charge applies
- ¹⁾ Throat depth frame only available with frame No. 7-600
- ²⁾ Increased throat and higher frame lead to smaler nominal forces for No. 311
- ³⁾ The weight was determined with hand lever position 45° forward (guide)
- ⁴⁾ Typical values; can vary ± 3 mm due to casting and production tolerances
- 5) Adjustable stroke

- Other available Options:
- Nickel plated cast parts are electroless nickel plated, steel components black oxide finished, aluminum anodized, precision steel surfaces are untreated
- Custom paint press and column can be painted to customer's color specification
- Bores for adapting tooling customer specific sizes can be supplied

SCHMIDT® ManualPress 300 Series

Options suitable for your application



Control mounting bracket

Used for fastening the **SCHMIDT® PressControl 700**, either mounted to the table or to the wall. The mounting bracket permits the unit to pivot 70° (included with control).



Calibration tool

The calibration tool is a device with which a constantly defined force is applied to the load cell of the **SCHMIDT**[®] **Manual-Press Serie 300** Series. In order to complete calibration, either a **SCHMIDT**[®] **LoadCheck** or a customer supplied calibration device is required. Photo on left side shows the device for the **SCHMIDT**[®] **ManualPress 305**. The right side is for **SCHMIDT**[®] **ManualPress 307**. The **SCHMIDT**[®] **ManualPress 311** is calibrated by using the fine adjustment mechanism in BDC.



Speed control

To achieve a very high repeatability when pressing to a force or stroke, the optional speed control can be added to provide hydraulic resistance to the ram movement over a targeted length at the end of the stroke.



External reset button

We recommend an external reset button in rough production environments.



EtherCAT Compact Box

8 digital channels, usable as inputs or outputs, signal connection by screwing via M8 plug connector, power supply (24 V) via EtherCAT-P, load currents of the outputs up to 0.5 A, total current of all outputs 3 A



Ergonomic handle

Swivelling handle for improved comfort; easy and flexible assembly on the hand lever.



Press base Plastic (250 x 340 mm), incl. fasteners.



SCHMIDT® PneumaticPress Maximum pressing force from 1.6 kN to 60 kN

The **SCHMIDT**[®] **PneumaticPress** range builds on a modular concept and can generate up to 60 kN. They are ideally suited for joining, assembly and forming applications.

With the addition of the **SCHMIDT**[®] **PressControl 75** or **700** and the optional process monitoring, these presses become EC typeapproved, CE-conformed workstations. Therefore these press systems can be used in either single cycle or automatic mode. The application determines the selection of the press system. Consideration is given to the flexible design of the assembly location, taking into account the ergonomic and safety aspects. These characteristics are achieved by means of a finely adjusted, modular type product range. The efficiency and increased process reliability of these press systems have been proven many times, in single applications, semi-automated assembly systems and have been integrated into automated production lines.



SCHMIDT[®] PneumaticPress

Example of a system design with a direct acting press



Cylinder unit

Maintenance-free specially developed for the assembly technology; with flow control for speed regulation of the downstroke.

2 Press Head unit

Modular design allows for quick and accurate height adjustment when installed on our column or the system can be easily integrated, in any orientation, to an automated press solution.

3 Pneumatic control package

Two-channel pneumatic package (as shown) is based on a modular valve block, designed to operate with filtered, non-lubricated air, supply pressure range of 3 – 6 bar.

4 Force control

The force output can easily be controlled via a regulator and pressure gauge.

5 Ram

With precision bore for tool holding and built-in, adjustable stop.

6 Frame

Robust design with precision machined keyway for press head alignment.

Fixture mounting plate

With precision T-slot and precision bore for tool location.

Force output preselector (optional)

The press force output can easily be controlled via a separate pressure regulator and pressure gauge. The pressure for the power stroke can be reduced to 1 bar



SCHMIDT[®] **PneumaticPress** Principle of operation

Functional description using a 3-chamber pneumatic cylinder – as an example.

In working stroke, three pistons 7 connected by the piston rod 6 are pressurized with compressed air via the air connection 1 and move downward. The air below the pistons exhausts from the cylinder chambers via the depressurized connection 2 and the breather vents 3 and 4. The ram 5 extends up to the maximum working stroke.

In return stroke, the upper cylinder chambers are depressurized via the connection **1** and only the bottom piston is pressurized with compressed air via the air connection **2**. Ambient air enters in both remaining cylinder chambers via the breather vents **3** and **4**. The ram with the three pistons moves upward.

This construction has the same effect as a parallel connection of three cylinders. Thus, a powerful working stroke is achieved with a compact design as well as an economic use due to the low air consumption in the return stroke.

The stroke can be limited by setting the Stroke Limit Block ⁽³⁾ to an approximate, desired position. The gap between Stroke Limit Block and Stroke Fine Adjustment ⁽⁹⁾ now determines the maximum stroke that the ram can travel. In order to fine-tune this stroke, fine adjustment nut ⁽⁹⁾ can be adjusted.

All direct acting presses have a built-in permanent magnet **1**. This magnet facilitates sensing of the ram position via tie rod mounted sensors.

Characteristics

- Optimally adapted to individual requirements due to its modular design
- Process optimization by means of adjustable parameters (stroke, force, speed)
- Easy adaptation to different tool and part heights because of simplistic stroke and height adjustment
- Additional safety measures when using heavy tools due to the optional device for retention of ram in home position
- End position control via cylinder switches as signal transmitter for peripheral processes
- Low noise level (< 75 dBA)</p>
- Double-acting, wear-resistant cylinders with low air consumption for the return stroke
- High flexibility due to short changeover time
- Long service life and high precision due to wear-resistant Teflon coated bushings at top and bottom of cylinder
- Precision ground ram
- Precision double ram guides



SCHMIDT[®] **PneumaticPress** Direct acting with constant force over the entire stroke

Characteristics

- Round anti-rotational ram
- Adjustable ram position in BDC by means of precision lower stop (1 division line = 0.05 mm) on scale
- T-slot with locking set screw in fixture mounting plate





Press Type 20

Press Type 23



Press Type 24



Press Type 25



Pneumatic cylinder with piston and magnet kit for ram position via cylinder switch.





From 1.6 kN to 12.5 kN

Press Type			20	23	24	25
Working stroke up to	A	mm	50, 75 100, 125 160, 200 250, 300	50, 75 100, 125 160, 200 250, 300	50, 75 100, 125 160	50, 75 100
Nominal force at 6 bar		kN	1.6	4.2	8.4	12.5
Throat depth	С	mm	86	86	86	86
Throat depth frame O		mm	111, 131 160, 200	111, 131 160, 200	111, 131 160, 200	111, 131
Additional fixture mounting plate suitable for throat depth frame			0	0	0	0
Ram bore	Ø	mm	20H7	20H7	20H7	20H7
Ram diameter	Ø	mm	40	40	40	40
Working height 1)	F					
Frame No. 3		mm	80-220	90-210	90-210	90-210
Frame No. 2 o		mm	110-360	120-350	120-350	120-350
Frame No. 2-600 o		mm	200-600	210-580	210-580	210-580
Frame No. 2-1000 o		mm	330-1040	335-1020	335-1020	335-1020
Weight	арр	rox. kg	30	35	40	45
Flange model			20-FL	23-FL	24-FL	25-FL
Cylinder	Z	Ømm	69	106	106	106
Flange	FL	Ømm	110	140	140	140
Width across flats	SW	mm	80	112	112	112
Centering shoulder	ZA	Ømm	60	68	68	68

Frame Overview	Press Type	Frame Height M (mm)	Table Size B x T (mm)	Table Bore D Ø mm	Table Height K (mm)	Mounting Surface B x L (mm)
No. 3	20, 23, 24, 25	540	150 x 110	20H7	60	150 x 260
No. 2	20, 23, 24, 25	700	185 x 110	20H7	60	185 x 280
No. 2-600 O	20, 23, 24, 25	974	200 x 160	20H7	98	200 x 290
No. 2-1000 o	20, 23, 24, 25	1410	200 x 160	20H7	98	200 x 290

Options

• Additional charge applies

 $^{\rm ()}$ Typical values; can vary \pm 3 mm due to casting and production tolerances

Other available options

- Nickel plated cast parts are electroless nickel plated, steel components black oxide finished, aluminum anodized, precision steel surfaces are untreated
- Custom Paint press and column can be painted to customer's color specification
- Bores for adapting tooling customer specific sizes can be supplied



Mounting drill pattern flange/ram





Detailed dimensional drawings can be downloaded: www.schmidttechnology.de

SCHMIDT[®] **PneumaticPress** Direct acting with constant force over the entire stroke

Characteristics

- Round anti-rotational ram
- Adjustable ram position in BDC by means of precision lower stop (1 division line = 0.05 mm) on scale





Press Type 27

Press Type 29

Precision lower stop





Height adjustment Fast, accurate setting of the work height.







From 7 kN to 43 kN

Press Type			27-1K	27-2K	27-3K	29-1K	29-2K	29-3K	29-4K
Working stroke up to	А	mm	50, 75, 100 160, 200 250, 300	50, 75 100, 125 160, 200	50, 75 100, 125 160	50, 75 100, 160 200, 300	50, 75 100, 125 160, 200	50, 75 100, 125 160	50, 75 100
Nominal force at 6 bar		kN	7	13	20	11	22	32	43
Throat depth	с	mm	131	131	131	140	140	140	140
Throat depth frame O		mm	151	151	151	160, 185	160, 185	160, 185	160
Additional fixture mounting plate suitable for throat depth frame			0	0	0	0	0	0	0
Ram bore	Ø	mm	20H7	20H7	20H7	20H7	20H7	20H7	20H7
Ram diameter	Ø	mm	40	40	40	50	50	50	50
Working height 1)	F								
Frame No. 34		mm	90-270	90-270	90-270				
Frame No. 301 o		mm	160-400	160-400	160-400				
Frame No. 301-500 o		mm	310-550	310-550	310-550				
Frame No. 29		mm				80-290	80-290	80-290	80 - 290
Frame No. 29-500 o		mm				150-500	150-500	150-500	150 – 500
Frame No. 29-600 O		mm				250-600	250-600	250-600	250 - 600
Weight (standard)	appr	ox. kg	85	85	85	120	120	120	120
Flange model			27-1K-FL	27-2K-FL	27-3K-FL	29-1K-FL	29-2K-FL	29-3K-FL	29-4K-FL
Cylinder	Z	Ømm	132	132	132	170	170	170	170
Flange	FL	Ømm	180	180	180	220	220	220	220
Width across flats	SW	mm	140	140	140	180	180	180	180
Centering shoulder	ZA	Ømm	68	68	68	80	80	80	80

Frame Overview	Press Type	Frame Height M (mm)	Table Size B x T (mm)	Table Bore D Ø mm	Table Height K (mm)	Mounting Surface B x L (mm)
No. 34	27	630	200 x 160	25H7	111	200 x 370
No. 301	27	830	250 x 200	40H7	145	250 x 460
Frame No. 301-500 o	27	990	250 x 200	40H7	145	250 x 480
Special fixture mounting plate with 3 longitudinal slots o			300 x 220 400 x 230	40H7 40H7		
Frame No. 29	29	690	300 x 220	40H7	141	300 x 460
Frame No. 29-500 o	29	990	300 x 220	40H7	166	300 x 540
Frame No. 29-600 O	29	1110	300 x 220	40H7	166	300 x 565
Special fixture mounting plate with 3 longitudinal slots O			355 x 225 400 x 230	40H7 40H7		

 $\overline{\oplus}$

 \oplus

 $^{\mbox{\tiny 1)}}$ Typical values; can vary \pm 3 mm due to casting and production tolerances

Other available options

- Nickel plated cast parts are electroless nickel plated, steel components black oxide finished, aluminum anodized, precision steel surfaces are untreated
- Custom Paint press and column can be painted to customer's color specification
- Bores for adapting tooling customer specific sizes can be supplied



Options

• Additional charge applies



Detailed dimensional drawings can be downloaded: www.schmidttechnology.de

SCHMIDT[®] PneumaticPress

Pneumatic Toggle Presses with maximum force at the end of stroke

Characteristics

- Cross hole with locking screw in the press table for safe fixture of tool
- Accurate adjustable ram position via fine adjustment (type 33)
- T-slot with set screw in fixture mounting plate to secure bottom tool





Press Type 32

Press Type 33



Fine adjustment for press No. 33 with scale 1 division line = 0.02 mm.



Flexible stroke adjustment reduces the air consumption for shorter strokes.





Up to 15 kN

Press Type			32	33
Working stroke up to	Α	mm	0-12 4-40 6-60	0-12 4-40
Nominal force at 6 bar		kN	15	15
Throat depth	с	mm	86	86
Throat depth frame O		mm	111, 131	111, 131
Additional fixture mounting plate suitable for throat depth frame			0	0
Ram bore	Ø	mm	20H7	20H7
External ram dimensions	Ø	mm	40	40
Fine adjustment				•
Working height ¹⁾	F			
Frame No. 3 O		mm	80 – 205	
Frame No. 5		mm	80 – 350	35 – 295
Frame No. 2-600 o		mm	200 – 575	155 – 520
Frame No. 2-1000 o		mm	330 – 1020	285 – 965
Weight	appro	ox. kg	45	50

Frame Overview	Press Type	Frame Height M (mm)	Table Size B x T (mm)	Table Bore D Ø (mm)	Table Height K (mm)	Mounting Surface B x L (mm)
No. 3	32	540	150 x 110	20H7	60	150 x 260
No. 5	32, 33	536	185 x 110	20H7	60	185 x 280
Frame No. 2-600 O	32, 33	810	200 x 160	20H7	98	200 x 290
Frame No. 2-1000 o	32, 33	1248	200 x 160	20H7	98	200 x 290

Options

- Series standard with no additional charge
- Additional charge may applies
- $^{1)}$ Typical values; can vary \pm 3 mm due to casting and production tolerances

Other available options

- Nickel plated cast parts are electroless nickel plated, steel components black oxide finished, aluminum anodized, precision steel surfaces are untreated
- Custom Paint press and column can be painted to customer's color specification
- Bores for adapting tooling customer specific sizes can be supplied



Detailed dimensional drawings can be downloaded: www.schmidttechnology.de

SCHMIDT® PneumaticPress

Pneumatic Toggle Presses with maximum force at the end of stroke

Characteristics

- Anti-rotational square ram with fully adjustable, Teflon lined gibs for precise travel, no die set required
- Exact positioning due to fine adjustment scale (1 division line = 0.05 mm)





Press Type 34

Press Type 36



Square ram



Fine adjustment

Pushing Force Diagram Operational pressure: 6 bar





From 28 kN to 60 kN

Press Type			34	36
Working stroke up to	Α	mm	0-12 4-40 6-60	0-12 4-40 6-60
Nominal force at 6 bar		kN	28	60
Throat depth	С	mm	131	160
Throat depth frame O		mm	151	185
Fixture mounting plate suitable for throat depth frame			0	0
Ram bore	Ø	mm	20H7	20H7
External ram dimensions	GxH	mm	36 x 63	46 x 86
Working height ¹⁾	F			
Frame No. 34		mm	100-250	
Frame No. 301		mm	160-400	
Frame No. 301-500		mm	310-550	
Frame No. 35		mm		100 - 250
Frame No. 35-500		mm		150-500
Frame No. 35-600		mm		250-600
Weight	ар	prox. kg	90	150

Frame Overview	Press Type	Frame Height M (mm)	Table Size B x T (mm)	Table Bore D Ø mm	Table Height K (mm)	Mounting Surface B x L (mm)
No. 34	34	630	200 x 160	25H7	111	200 x 370
No. 301	34	830	250x200	40H7	145	250 x 460
No. 301-500	34	990	250x200	40H7	145	250 x 480
Special fixture mounting plate with 3 longitudinal slots O			300 x 220 400 x 230	40H7		
No. 35	36	700	300 x 220	40H7	141	300 x 480
No. 35-500	36	990	300 x 220	40H7	166	300 x 560
No. 35-600	36	1110	300 x 220	40H7	166	300 x 585
Special fixture mounting plate with 3 longitudinal slots o			355 x 225 400 x 280	40H7		

Options

- o Additional charge applies
- ¹⁾ Typical values; can vary \pm 3 mm due to casting and production tolerances

Other available options

- Nickel plated cast parts are electroless nickel plated, steel components black oxide finished, aluminium anodized, precision steel surfaces are untreated
- Custom Paint press and column can be painted to customer's color specification
- Bores for adapting tooling customer specific sizes can be supplied



Detailed dimensional drawings can be downloaded: www.schmidttechnology.de

SCHMIDT[®] PneumaticPress Direct acting Pneumatic Presses with force/stroke monitoring

SCHMIDT® PneumaticPresses with force/stroke monitoring are offered as complete systems with the **SCHMIDT®** PressControl 700 and 7000. These systems are characterized by sensors and signal amplification integrated in the press head. These signals are evaluated in real time.

Characteristics

- Direct forces are measured due to the force sensor integrated in the ram. Insensitive against side loads
- Force and displacement sensors are immune to EMI and environ-mental contamination
- A measuring data amplification integrated in the press head provides short transmission paths of unamplified signals
- Anti-rotational square ram with two fully adjustable guiding gibs for precise work and for non-guided tools
- Weld constructed steel frames to minimize frame flex.



Press Type 327, 329





From 1.6 kN to 43 kN

Press Type			327-3K	329-2K	329-3K	329-4K
Working stroke up to	Α	mm	50, 75, 100	50, 75, 100, 150	50, 75, 100, 125, 150	50, 75, 100
Nominal force at 6 bar		kN	20	22	32	43
Resolution, process data acquisition						
- stroke		µm/inc	5	5	5	5
- force		N/inc	6.25	6.25	10	12.5
Throat depth	С	mm	131	160	160	160
Throat depth frame O		mm	151			
Fixture mounting plate suitable for throat depth frame			0			
Ram bore	Ø	mm	20H7	20H7	20H7	20H7
External ram dimensions	GxH	mm	70 x 50	90 x 60	90 x 60	90 x 60
Working height 1)	F					
Frame No. 7-420		mm				
Frame No. 7-600 o		mm				
Frame No. 301		mm	140 – 350			
Frame No. 301-500 o		mm	310 – 500			
Frame No. 329		mm		130 – 300	130 – 300	130 – 300
Frame No. 329-460 O		mm		190 – 460	190 – 460	190 – 460
Weight (standard)		approx. kg	170	320	325	330

Frame Overview	Press Type	Frame Height M (mm)	Table Size B x T (mm)	Table Bore DØmm	Table Height K (mm)	Mounting Surface B x L (mm)
No. 301	327	830	250 x 200	40H7	145	250 x 460
No. 301-500	327	990	250 x 200	40H7	145	250 x 480
Special fixture mounting plate with 3 longitudinal slots ²⁾ O			300 x 220 400 x 230	40H7		
No. 329	329	810	300 x 230	40H7	147	300 x 550
No. 329-460	329	990	300 x 230	40H7	147	300 x 620
Special fixture mounting plate with 3 longitudinal slots ²⁾ O			400 x 280 500 x 280	40H7		

Options

- Additional charge applies
- ¹⁾ Typical values; can vary ± 3 mm due to casting and production tolerances

Other available options

- Nickel plated cast parts are electroless nickel plated, steel components black oxide finished, aluminium anodized, precision steel surfaces are untreated
- Custom Paint press and column can be painted to customer's color specification
- Bores for adapting tooling customer specific sizes can be supplied

Bottom view of the press head

Fastening drill pattern flange/ram Press Type 327

Press Type 329









Detailed dimensional drawings can be downloaded: www.schmidttechnology.com




SCHMIDT® HydroPneumaticPress Maximum force range from 15 kN to 220 kN

The **SCHMIDT**[®] **HydroPneumaticPress** range builds on a modular concept and can generate up to 220 kN. They are ideally suited for joining, assembly and forming applications. With the addition of the **SCHMIDT**[®] **PressControl 75** or **700** and the optional process monitoring, these presses become EC type-approved, CE-conformed workstations. Therefore these press systems can be used in either single cycle or automatic mode.

The application determines selection of the press system. Consideration is given to the flexible design of the assembly location taking into account the ergonomic and safety aspects. These characteristics are achieved by means of a finely adjusted, modular type product range. The efficiency and increased process reliability of these press systems have been proven many times, in single applications, semi-automated assembly systems and have been integrated into automated production lines.



SCHMIDT[®] HydroPneumaticPress

System design





Stroke feedback

Ram with key-ways for switch target pieces for an inductive position feedback. Optional: Stroke-dependent activation of the power stroke by means of the proximity switch. 1 Cylinder unit Hydro pneumatic

Flow control rapid approach stroke For speed control of the downstroke

3 Press head unit

Modular design allows for quick and accurate height adjustment when installed on our column or the system can be easily integrated, in any orientation, to an automated press solution.

4 Pneumatic control package

Two-channel pneumatic package (as shown) is based on a modular valve block

5 Force output preselector

The press force output can easily be controlled via a separate pressure regulator and pressure gauge. The pressure for the power stroke can be reduced to 1 bar

6 Square ram

Square ram with precision machine bore and fully adjustable Teflon line gibs for precise ram guidance.

7 Frame

With precision machined press head guide rails (for **No. 68** and **368** designed as dovetail guide)

Fixture mounting plate

With precision T-slot and precision bore for tool location



SCHMIDT[®] HydroPneumaticPress

Principle of operation



Rapid approach stroke

In rapid approach stroke, the air connections 1 and 4 are pressurized with compressed air. The air connections 2 and 3 are depressurized. The approach stroke piston 6 and the reservoir piston 7 are moving with low force until the ram 5 encounters resistance.

Power Stroke

If the ram **5** encounters resistance, a valve switches the compressed air from **4** to connection **3**, and the power stroke piston **8** moves downwards. A rod enters the high pressure cylinder, separating the hydraulic oil between reservoir piston **7** and approach stroke piston **6**. The ram **5** moves out with boosted force.

Return Stroke

For the return stroke, the connections 1 and 3 are depressurized, and the connections 2 and 4 are pressurized. Approach stroke 6 and power stroke piston 8 move back simultaneously. After the hydraulic connection between approach 6 and reservoir piston 7 oil flows back into the reservoir, moving the reservoir piston into its home position.

Characteristics

- Optimally adapted to individual requirements due to its modular design
- High flexibility and economic efficiency due to short changeover times
- Easy and accurate positioning of tools due to the precise alignment between ram bore and the ground fixture mounting plate.
- The force output preselector allows reducing the pressure for the power stroke to 1 bar. This reduces the nominal press force to 1/6 of the maximum force.
- The end positions of the ram can be sensed via the inductive proximity switches.
- No mechanical compression spring in the cylinder of the hydropneumatic system, providing a long service life
- Low maintenance resulting in high productivity
- Long service life and precision due to maintenance-free guides
- Tool protection due to smooth switchover from rapid approach stroke to power stroke
- Additional safety when using heavy tools due to the optional ram drift lock device for retention of ram in home position.
- Low noise level (< 75 dBA)

SCHMIDT[®] HydroPneumaticPress C-Frame design

Characteristics

- The C-Frame design offers full accessibility when manually inserting and removing parts
- Easy adaptation to different tool and part heights because of simplistic height adjustment with angular gear
- Anti-rotational square ram with fully adjustable, Teflon lined gibs for precise travel. No die set required
- High precision due to long precise guides of the square ram





Press type 61/62







Power stroke





Square ram

with bilaterally adjustable, play-free gibs, precision machined bore with set screw for mounting of tooling.



Operational pressure < 3 bar: can only be operated with press force preselector!



From 15 kN to 52 kN in power stroke

Press Type			61	62	65
Total stroke – power stroke 1)		mm	50 – 6, 100 – 12	50 – 6, 100 – 12	50 – 6, 100 – 12
Nominal force at 6 bar		kN	15	30	52
Throat depth	С	mm	131	131	160
Throat depth frame o		mm	151	151	185
Fixture mounting plate suitable for throat depth frame			0	0	0
Ram bore	Ø	mm	20H7	20H7	20H7
External ram dimensions	GхН	mm	36 x 63	36 x 63	46 x 86
Working height ²⁾	F				
Frame No. 34		mm	100 – 250	100 – 250	
Frame No. 301 o		mm	160 - 400	160 - 400	
Frame No. 301-500 o		mm	310 - 550	310 – 550	
Frame No. 35		mm			80 - 270
Frame No. 35-500 o		mm			150 - 500
Frame No. 35-600 o		mm			250 - 600
Weight (standard)	арр	rox. kg	95	110	160

Frame Overview	Press Type	Frame Height M (mm)	Table Size B x T (mm)	Table Bore DØmm	Table Height K (mm)	Mounting Surface B x L (mm)
No. 34	61, 62	630	200 x 160	25H7	111	200 x 370
No. 301	61, 62	830	250 x 200	40H7	145	250 x 460
No. 301-500	61, 62	990	250 x 200	40H7	145	250 x 480
Special fixture mounting plate with 3 longitudinal slots O			300 x 220 400 x 230	40H7		
No. 35	65	700	300 x 220	40H7	141	300 x 480
No. 35-500	65	990	300 x 220	40H7	166	300 x 560
No. 35-600	65	1110	300 x 220	40H7	166	300 x 585
Special fixture mounting plate with 3 longitudinal slots O			355 x 225 400 x 280	40H7		

Options

• Additional charge applies

- ¹⁾ Total stroke / power stroke options on request
- $^{\rm 2)}$ Typical values; can vary \pm 3 mm due to casting and production tolerances



Detailed dimensional drawings can be downloaded: www.schmidttechnology.de

SCHMIDT[®] HydroPneumaticPress C-Frame design with welded press frame

Characteristics

- The welded press frame offers highest stability
- Space-saving and compact due to separate working cylinder for press No. 68





Press type 68

Press type 64



Power stroke







Return stroke



Operational pressure < 3 bar: can only be operated with press force preselector!

Square ram

with bilaterally adjustable, play-free gibs, precision machined bore with set screw for mounting of tooling. Some models feature additional provisions for tooling adaption.

Fixture mounting plate (for Press No. 64) with 3 T-slots and precision machined bore for tool location.



From 72 kN to 100 kN in power stroke

Press Type			64	68
Total stroke - Power stroke ¹⁾		mm	50-6, 100-12	50-6, 100-12
Nominal force at 6 bar		kN	100	72
Throat depth	С	mm	160	160
Ram bore	E	Ømm	25H7	20H7
External ram dimensions	GxH	mm	60 x 90	60 x 90
Working height 3)	F			
Frame No. 64		mm	180-350	
Frame No. 64-600 O		mm	430-600	
Frame No. 68 ²⁾		mm		130-300
Frame No. 68/5 ²⁾ O		mm		190-460
Weight (standard)		approx. kg	420	350

Frame Overview	Press Type	Frame Height M (mm)	Table Size B x T (mm)	Table Bore DØmm	Table Height K (mm)	Mounting Surface B x L (mm)
No. 64	64	940	400 x 290	40H7	185	400 x 625
No. 64-600 o	64	1200	400 x 290	40H7	185	400 x 685
No. 68 ²⁾	68	810	300 x 230	40H7	147	300 x 550
No. 68/5 ²⁾ o	68	990	300 x 230	40H7	147	300 x 620
Special fixture mounting plate with 3 longitudinal slots O			400 x 280 500 x 280	40H7		

Options

• Additional charge applies

¹⁾ Total stroke / power stroke options on request

²⁾ Frame 68/5 required for 30 mm power stroke

³⁾ Typical values; can vary ± 3 mm due to casting and production tolerances

Bottom view of the press head Mounting drill pattern flange/ram

Press type 64









Detailed dimensional drawings can be dowanloaded: www.schmidttechnology.de

SCHMIDT[®] HydroPneumaticPress C-Frame design with force/stroke monitoring

SCHMIDT[®] HydroPneumaticPresses with force / stroke monitoring are offered as complete systems with control unit SCHMIDT® PressControl 700 and 7000. These systems are characterized by sensors and signal amplification integrated in the press head. These signals are evaluated in real time.

Characteristics

- Direct forces are measured due to the force sensor integrated in the ram. Insensitive against side forces
- Signal readings are not affected by outside interference
- A measuring data amplification integrated in the press head provides short transmission paths of unamplified signals
- Precision guide rails for precise working. Bilaterally adjustable, play-free gibs, precision machined bore for tool location. No die-set required
- Weld constructed steel frames to minimize frame flex.





Press type 361

Press type 362

Press type 365



Power stroke



Return stroke



Operational pressure < 3 bar: can only be operated with press force preselector!



From 15 kN to 52 kN in power stroke

Press Type			361	362	365
Total stroke - Power stroke 1)		mm	50-6, 100-12	50-6, 100-12	50-6, 100-12
Nominal force at 6 bar		kN	15	30	52
Process data acquisition stroke force		µm/inc N/inc	5 4.5	5 9	5 15
Throat depth	с	mm	131	160	160
Throat depth frame o			151		
Fixture mounting plate suitable for throat depth frame			0		
Ram bore	Ø	mm	20H7	20H7	20H7
External ram dimensions	GxH	mm	70 x 50	90 x 60	90 x 60
Working height 2)	F				
Frame No. 301		mm	160-355		
Frame No. 301-500 o		mm	310-500		
Frame No. 329		mm		130-300	130-300
Frame No. 329-460 o		mm		190-460	190-460
Weight (standard)	ар	prox. kg	170	320	330

Frame Overview	Press Type	Frame Height M (mm)	Table Size B x T (mm)	Table Bore DØmm	Table Height K (mm)	Mounting Surface B x L (mm)
No. 301	361	830	250 x 200	40H7	145	250 x 460
No. 301-500 o	361	990	250 x 200	40H7	145	250 x 480
Special fixture mounting plate with 3 longitudinal slots O			300 x 220 400 x 230	40H7		
No. 329	362, 365	810	300 x 230	40H7	147	300 x 550
No. 329-460 o	362, 365	990	300 x 230	40H7	147	300 x 620
Special fixture mounting plate with 3 longitudinal slots O			400 x 280 500 x 280	40H7		

Options

• Additional charge applies

¹⁾ Total stroke / power stroke options on request

 $^{\rm 2)}$ Typical values; can vary \pm 3 mm due to casting and production tolerances

Bottom view of the press head

Mounting drill pattern flange/ram







Detailed dimensional drawings can be downloaded: www.schmidttechnology.de

SCHMIDT® HydroPneumaticPress In C-Frame design with force/stroke Monitoring

SCHMIDT[®] HydroPneumaticPress with force/stroke monitoring are offered as complete systems with control unit SCHMIDT[®] PressControl 700 and 7000. These systems are characterized by sensors and signal amplification integrated in the press head. These signals are evaluated in real time.



- Direct forces are measured due to the force sensor integrated in the ram. Insensitive against side forces
- Signal readings are not affected by outside interference
- A measuring data amplification integrated in the press head provides short transmission paths of unamplified signals
- Precision bilaterally adjustable, play-free gibs, precision ground bore for tool location. No die-set required
- Weld constructed steel frames to minimize frame flex.

SCHMIDT



Press type 364

Rapid approach stroke



Power stroke



Return stroke

Press type 368





From 72 kN to 100 kN in power stroke

Press Type			364	368
Total stroke - Power stroke 1)		mm	50-6, 100-12	50-6, 100-12
Nominal force at 6 bar		kN	100	72
Process data acquisition Stroke Force		µm/inc N/inc	5 32	5 20
Throat depth	С	mm	160	160
Ram bore	E	Ø mm	25H7	20H7
External ram dimensions	GxH	Ømm	90 x 60	90 x 60
Working height 3)	F			
Frame No. 64		mm	180-350	
Frame No. 64-600 O		mm	430-600	
Frame No. 68 ²⁾		mm		130-300
Frame No. 68/5 ²⁾ o		mm		190-460
Weight (standard)		approx. kg	420	350

Frame Overview	Press Type	Frame Height M (mm)	Table Size B x T (mm)	Table Bore DØmm	Table Height K (mm)	Mounting Surface B x L (mm)
No. 64	364	940	400 x 290	40H7	185	400 x 625
No. 64-600 O	364	1200	400 x 290	40H7	185	400 x 685
No. 68 ²⁾	368	810	300 x 230	40H7	147	300 x 550
No. 68/5 ²⁾ 0	368	990	300 x 230	40H7	147	300 x 620
Special fixture mounting plate with 3 longitudinal slots O			400 x 280 500 x 280	40H7		

Options

• Additional charge applies

¹⁾ Total stroke / power stroke options on request

²⁾ Frame 68/5 required for 30 mm power stroke

 $^{\scriptscriptstyle 3)}$ Typical values; can vary \pm 3 mm due to casting and production tolerances

Bottom View of the Press Head Mounting drill pattern flange/ram

Press Type 364

Press Type 368







Detailed dimensional drawings can be downloaded: www.schmidttechnology.de

SCHMIDT[®] HydroPneumaticPress H-Frame design with and without force/stroke monitoring



Press type 74/76 374/376 (with force/stroke monitoring)

Rapid approach stroke



Power stroke



Characteristics

- Stable frame with low bending for the absorption of high forces
- Flexible tool location in the fixture mounting plate due to
- replaceable centering bushing with precision bore • The large working area offers sufficient space for large tools
- The force is determined via a pressure transducer with force/ stroke monitored presses

Round ram locked against rotation with TDC switch (74/76) or position measuring system (374/376) on the anti-rotational guide rod.







Return stroke

14.4





From 100 kN to 220 kN in power stroke

Press Type			7	4	76	
Total stroke – power stroke ¹⁾		mm	100-12	150-22	100 – 12	150 – 20
Nominal force at 6 bar		kN	100	100	220	220
Ram bore	G	Ømm	25 ^{H7}	25 ^{H7}	32 ^{H7}	32 ^{H7}
External ram dimensions		Ømm	90	90	90	90
Working height 2)	F		350	350	350	350
Press head height	SH		919	1181	1157	1400
Frame hight	К	mm	78	78	78	78
H-frame height	М	mm	692	692	692	692
Floor space required	ВхТ	mm	630 x 440	630 x 440	630 x 440	630 x 440
Table size	ВхТ	mm	370 x 300	370 x 300	370 x 300	370 x 300
Table bore	D	Ømm	40 ^{H7}	40 ^{H7}	40 ^{H7}	40 ^{H7}
Clearance	С	mm	490	490	490	490
Clearance side	I	mm	220	220	220	220
Weight (standard)		approx. kg	550	605	610	665
Press Type			374		3	76
Total stroke – power stroke ¹⁾		mm	100-12	150 – 22	100-12	150 – 20
Nennkraft bei 6 bar		kN	100	100	220	
Process data acquisition						
– stroke		µm/inc	5	5	5	5
– force		N/inc	32	32	62,5	62,5
Ram bore	G	Ømm	25 ^{H7}	25 ^{H7}	32 ^{H7}	32 ^{H7}
External ram dimensions		Ømm	90	90	90	90
Working height ²⁾	F		350	350	350	350
Press head height	SH		919	1181	1157	1400
Frame hight	К	mm	78	78	78	78
H-frame height	M	mm	692	692	692	692
Floor space required	ВхТ	mm	630 x 440	630 x 440	630 x 440	630 x 440
Table size	B1 x T1	mm	370 x 300	370 x 300	370 x 300	370 x 300
Table bore	D	Ømm	40 ^{H7}	40 ^{H7}	40 ^{H7}	40 ^{H7}
Clearance	С	mm	490	490	490	490
Clearance side	I	mm	220	220	220	220
Weight (standard)		approx. kg	550	605	610	665

Options

¹⁾ Total stroke / power stroke options on request

 $^{\rm 2)}$ Typical values; can vary ±3 mm due to casting and production tolerances

Accessories



High-pressure switch

After switching from rapid approach stroke to power stroke, the oil pressure rises in the hydraulic chamber of the cylinder. The high-pressure switch can be adjusted to reach a determined press force through the output generated by the oil pressure in the press.

Adjustment bushing for SCHMIDT[®] HydroPneumatic-Press No. 74 and 76

For a simplistic adjustment of the working height with a setting range of 100 mm. This greatly reduces the need for spacers to accommodate different working heights during setup changes.

For an air-free refilling of the **SCHMIDT®** HydroPneumatic-Press with hydraulic oil, including 1 liter Hydraulic oil.

Oil pump

SCHMIDT[®] Cylinder Units For flexible use

SCHMIDT[®] Double-acting **cylinder units** are useful components for the construction of special machines. They can be mounted independently and are equipped with a magnet kit for detecting the corresponding end position using a cylinder switch. Direct

acting air provided as flange or side-mount models and toggle or hydropneumatic type as side mount models, achieving forces up to 100 kN.

Press head (side-mount) model

Flange model

Technical Data	SCHMIDT® Cylinder Units					
Typ No.	Press head model	Flange model				
20 - 29	•					
32 - 36	•					
61 - 68	•	(not for No. 61 , 62 , 65)				
323 - 368	•	•				

For the performance data, please refer to the chapters **SCHMIDT**[®] **PneumaticPress** and **SCHMIDT**[®] **HydroPneumaticPress**, optional with force/stroke monitoring.

Order indications

Key for design options

Cylinder unit / stroke / design

Order example	head 65 - 50 - 6
Press no.	
Total stroke	
Power stroke	

Cylinder	unit /	stroke /	design
Cymruci	unit,	JUOKC /	ucsign

Order exam	ole	20 - 50	- FL
Press no.			
Stroke			
Model			

= SCHMIDT[®] Cylinder Unit No. 65 with total stroke 50 mm and power stroke 6 mm as press head model

= SCHMIDT® Cylinder Unit no. 20 with stroke 50 mm as flange model

SCHMIDT® ElectricPress A new approach to assembly technology

The use of electric drives instead of pneumatic or hydropneumatic driven cylinders is a modern advancement in assembly technology. **SCHMIDT Technology** combined its proven rack & pinion and ServoPress experience to create a new electric drive technology, providing high efficiency, full programmability and precision in a flexible pressing system.

The success of your products depends to the highest degree on process-reliable and, above all, economical assembly:

- process-safe due to reliable quality statements
- economical due to a significant reduction in operating costs thanks to electric motor drive technology.

The synergy of both criteria is fulfilled by the press system **SCHMIDT**[®] **ElectricPress** with up to **20 kN** maximum force and the controls **SCHMIDT**[®] **PressControl 75** for **SCHMIDT**[®] **ElectricPress 43** and **45** or **SCHMIDT**[®] **PressControl 700x** for the force-displacement monitored systems. These well-known and proven components for robust use in automation technology guarantee exactly this success.

The key advantage of the SCHMIDT® ElectricPress:

- Simple parameterisation minimises commissioning time
- Quick changeover procedures due to retrievable operating profiles
- Increased flexibility
- Cost reduction of tools and their wear due to free, precise positioning.
- The low noise level provides a stress-free working environment.
- The design-related non-existent stick-slip effect optimises the assembly process compared to pneumatic drives, especially at low speeds.

The expected high quality demands are met not least on the test bench. To determine the typical service life of 2×10^7 press cycles, the test was based on minimum requirements. The mechanical, electrical and motor components as well as the thermal behaviour of the entire system passed this stress test with flying colours.

- Reproducible travel profiles
- High energy efficiencySimple integration
- Purely electric drive
- Height adjustable

SCHMIDT[®] ElectricPress 43/45 with PressControl 75

SCHMIDT® ElectricPress manual workstation with **SafetyModule** on PU 20

SCHMIDT® PressControl 75 for quick set-up or rapid changeover and easy programming of press parameters; stores up to 24 datasets for us in manual workcells with **SCHMIDT Technol**ogy's proven and certified safety technology.

This combination can be used both in manual workstations as well as in automation solution.

Characteristics: Reproducible v

- Reproducible values for position, velocity, acceleration and deceleration
- Combination of up to 14 individual ram motion profiles into one complete profile by using a standard PLC
- Press to exact position (closed loop control stroke)
- Press to force (determined by motor current) to
 - press to final force
 - press to position but interrupt if force is exceeded
 - touch force to determine position of workpiece

SCHMIDT® ElectricPress 43 automation

SCHMIDT[®] ElectricPress 343/345 with PressControl 700/7000

Paired with a **SCHMIDT**[®] **PressControl 700** or **PressControl 7000** the ElectricPress becomes a force/stroke monitored system. Its closed-loop force and position control ensures highest accuracy and facilitates the programming of complex ram motion profiles for a wide variety of pressing applications.

In addition to the position controller, **SCHMIDT**[®] **ElectricPress** also works with a real force controller (force as a controlled variable).

- Rapid approach of target force or position
- No over-shoot of programmed force or position
- Positioning accuracy in a range of 1/100 mm under constant loads
- Perfectly adapts to each application
- Pre-programmed with optimal acceleration/deceleration values
- Graphic display of force/time and stroke/time facilitates cycle time optimization

Single workstations

In conjunction with type-examined safety techniques two-hand release, light curtain and SCHMIDT[®] SmartGate

Automation

SCHMIDT[®] ElectricPress 343, 345 and 347 with SCHMIDT[®] PressControl 7000 control for automation solution

Process visualization

SCHMIDT[®] ElectricPress 347 automation

SCHMIDT® ElectricPress Technical Data 43/343/45/345

Press Type			43	343	45	345
Force F max. ¹⁾		kN	4	4	10	10
Force F at 100 % duty cycle ²⁾		kN	2,5	2,5	6	6
Ram stroke	А	mm	100	100	150	150
Ram speed max.		mm/s	200	200	200	200
Drive resolution		μm	< 1	< 1	< 1	< 1
Resolution PDA						
- Stroke		µm/inc		1,69		2,4
- Force		N/inc		1,25		3,0
Throat depth	С	mm	129	129	129	129
Decibel level		dBA	60	60	60	60
Power supply						
- motor power			208 – 240 V AC ±10 %	208 – 240 V AC ±10 %	208 – 240 V AC ±10 %	208 – 240 V AC ±10 %
- logic unit			24 V DC / 2 A	24 V DC / 2 A	24 V DC / 2 A	24 V DC / 2 A
Working height frame 7-420 ³⁾	E	mm	62 – 420	62 – 420	50 – 360	50 - 360
Working height frame 7-600 ³⁾	Г	111111	100 - 610	100 - 610		
S-H x S-B x S-T		mm	402 x 207 x 385	402 x 240 x 385	530 x 245 x 410	530 x 275 x 410
Weight		kg	35	35	59	59
PRC Gateway, number of I/O's				16 inputs / 16 outputs		16 inputs / 16 outputs

Frame Overview	Press Type	Frame Height M (mm)	Table Size B x T (mm)	Table Bore D Ø (mm)	Table Height K (mm)	Mounting surface (mm)	
No. 7-420	43, 343, 45, 345	740	180 x 150	20 ^{H7}	90	220 x 362	
No. 7-600	43, 343	960	180 x 280	20 ^{H7}	110	220 x 465	

¹⁾ Temporary peak load

²⁾ Nominal power in continuous operation

 $^{\scriptscriptstyle 3)}$ Typical values; can vary ± 3 mm due to casting and production

tolerances

Ram press type 43

Ram press type 343

Ram press type 45

Ram press type 345

SCHMIDT® ElectricPress Technical Data 347

Press type			347
Force F max. 1)		kN	20
Force F at 100 % duty cycle 2)		kN	13
Ram stroke	А	mm	150
Ram stroke max.		mm/s	100
Drive resolution	E	μm	< 1
Resolution PDA – stroke – force		µm/inc N/inc"	2,30 6,25
Throat depth	С	mm	160
Decibel level		dB A	66
Power supply – motor power – logic unit			208 – 240 V AC ±10 % 1.3 kW 24 V DC / 2 A
Working height frame 35 ⁻³⁾ frame 35-500 ⁻³⁾ frame 35-600 ⁻³⁾	F	mm	18 – 225 80 - 495 196 - 612
S-H x S-B x S-T		mm	464 x 298 x 261
Weight		kg	66
PRC Gateway, number of I/O's			16 inputs / 16 outputs

Frame overview	Press type	Frame Height M (mm)	Table Size W x D (mm)	Table Bore D (Ø mm)	Table Height K (mm)	Mounting Surface W x L (mm)	Frame Weight (kg)
No. 35	347	688/(846) ⁶⁾	300 x 220	40H7	141	300 x 475	99
No. 35-500	347	983/(1371) ⁶⁾	300 x 220	40H7	166	300 x 560	213
No. 35-600	347	1100/(1488) ⁶⁾	300 x 220	40H7	166	300 x 590	242

¹⁾ Temporary peak load

²⁾ Nominal power in continuous operation

 $^{\scriptscriptstyle 3)}$ Typical values; can vary \pm 3 mm due to casting and production tolerances

⁶⁾ incl. threaded rod Höhenverstellung

SCHMIDT[®] **ServoPress** Forces from 1 kN bis 250 kN

An efficient assembly process is crucial for the success of your company. Parts with individual tolerances must be joined to create an accurate assembly. Electrically driven screw type actuators (servo presses) are ideally suited for this task. The high precision SCHMIDT[®] ServoPress paired with a specifically designed SCHMIDT® PressControl 700 or 7000 offers the perfect solution both as a single work cell or in an automated assembly line, combining full closed loop force and position control with full force and distance monitor.

All SCHMIDT[®] ServoPress modules are designed to press to their full load capacity, incorporate ram position measurement technology, integrated load cells, automatic spindle greasing and have a built-in overload protection clutch (except No. 605). When equipped with our light curtain/guarding, SmartGate or Smart-Guard safety options, they meet the most current EC machinery directives for safety and can be provided with type approval documentation if required.

Press type 620

Press type 650/655/660/680

SCHMIDT® ServoPress Modules for a broad range of applications

The unrivaled solid construction of the **SCHMIDT**[®] **ServoPress** is the foundation for precision assembly results, even in the most rugged industrial environments.

Test bench validated

Before released for serial production, each newly designed press module undergoes test bench validation under the harshest of conditions. It is this testing that provides valuable insights for improvement of the design. A test run consist of 20 million cycles with maximum stroke, at full speed and pressing to full force while subjecting the ram to side loads.

Direct ram stroke measuring system

Precision sensor and scale integrated into the press module for direct ram stroke measurement. Tied directly to the PLC/CNC of the system for positioning based on ram location.

- Micron level positioning repeatability thanks to high resolution
- Compression compensation under full load
- Correction of ball bearing pitch inaccuracies
- Temperature related material expansions/contractions do not impact measuring results
- High resolution position feedback for process monitoring

Integrated load cell

Load cell tied into the control of the system to provide:

- True closed loop force control of the ram movement.
- No overshoot of the programmed force
- A constant force regardless of part / environment / system changes.
- True force feedback for process monitoring

Nominal force of module available

- 100 % of the time
- At any ram position
- For any duration
- Maximum force available in S3 Mode

System Protection

- Automatic spindle lubrication system
- Overload protection clutch (except ServoPress 605)
- Active cooling and thermal monitoring of electronic and mechanical components
- Current limiter

Maintenance friendly

- Automatic spindle lubrication system
- Integrated used grease depot
- No filters
- Plug-and-play module recognition

Integrated and EC type-approved operator safety with light-curtain, SmartGate and SmartGuard work cells.

ServoPress 650, 655, 660 and 680 are equipped with brake energy recuperation technology.

What does this mean for you?

- Highest degree of efficiency
- Maximum operational availability
- Highest reliability

Modules With force from 1 kN to 250 kN

Press type		605		616	61	7		620	650	655		660	680
Force E max S3 25 % 20 s	kΝ	1		5 14			35	75	110		160	250	
Force F 100 % continuous run	kN	0.5		3	7	5		20	50	80		110	200
Ram stroke	mm	150		200	30	200		400	500	500		350	350
Resolution position control	um	0.1		0.1	0	1		0.1	0.1	0.1		0.1	0.1
Ram speed	mm/s	0 - 300		0 - 200	0 -	200	() = 200	0 -200	0 -10	0 0	- 100	0 - 50
Resolution PDA force	N/inc	0 3		15	3	75		10	74	32		48	75
Resolution PDA stroke	um/inc	2.2		3.2	4	6		61	7.6	7.6		54	54
Overload protection	pinine	none		mechanic	al mech	anical	me	chanical	mechanical	mechan	ical med	hanical	mechanical
Drive				ball screv	N					planetary roll	er screw		
Weight appr.	kg	11.6		25	6	4		113	225	225		283	283
Tool weight max.	kg	5		15	2	5		50	100	100		100	100
Power supply (50 – 60 Hz)	V AC	208 – 24	0	208 – 24	400 - 4	180, 3~	400	- 480, 3~	400 - 480, 3-	~ 400 - 480), 3~ 400 -	480, 3~ 4	100 - 480, 3~
	mm	636/89/	155	599 / 124	1/ 892/	144 /	10	77 / 190	1250 / 243	1250/2	243 124	9/249	1249 / 249
		0507057	155	258	31	8		/ 384	/ 561	/ 561	/	552	/ 552
Ram bore	mm	6 ^{H7}		10 ^{H7}	20) ^{H7}		20 ^{H7}	20 ^{H7}	20 ^{H7}		20 ^{H7}	20 ^{H7}
Ram dimension	mm	Ø 25		Ø 40	□ 4	12		□ 55	□ 65	□ 65	<u> </u>	ð 90	Ø 90
Overall dimensions with	frame				605	616	6	617	620	650	655	660	680
Throat depth			C	mm	130	130)	150	160	160	160	160	160
Table bore			D	mm	а 20 ^{н7}	g 20 ¹	H7	а 40 ^{н7}	α 40 ^{H7}	а 40 ^{н7}	а 40 ^{н7}	а 40 ^{н7}	Ø 40 ^{H7}
Working height (ServoPress 6)	80 in H-fra	me-version)	F	mm	246	300)	387	518	612	507	500	500
Table height	00 1111 110	inte versioni,	K	mm	93	113	3	128	155	190	220	220	178
Table size			BxT	mm	160 x 140	220 x 1	175	250 x 200	300 x 200	370 x 230	370 x 230	370 x 23	0 370 x 230
Frame depth (ServoPress 680	in H-fram	e-version)	SL 6	mm	365	405	5	460	563	636	725	761	614
Frame height (ServoPress 680) in H-fram	ne-version)	SH 1	mm	510	630)	780	1080	1050	1050	1097	942
Total height			SH 2	mm	1015	1062	2	1467	1810	2012	2032	2036	2062
Weight appr.				kg	45	101		166	334	553	757	805	867
Housing													
			А	mm	574	535	5	800	957	1130	1130	1249	1249
			В	mm	155	252	2	318	384	555	555	552	552
			С	mm	62	119)	165	210	260	260	200	200
			D	mm	89	124	1	144	190	244	244	249	249
Cable connection													
			E	mm	105		497 2		256	823	823	370	370
			F	mm	~60	~60)	~60	~60	~60	~60	~60	~60
Flange													
			G	mm	62	63.5	5	92	120	120	120	-	-
			Н	mm	75	75		130	140	150	150	230	230
			J	mm 1)	60	88		120	160	210	210	130/210) 130/210
			I	mm	75	109)	134	180	235	235	230	230
			Κ	mm 1)	60	63		115	120	130	130	130	130
			L	mm 1)	40	59.4	4	75	-	-	-	-	-
			Μ	ø mm	45 ^{h6}	45 ^{h6}	6	65 ^{h6}	90 ^{h6}	100 ^{h6}	100 ^{h6}	120 ^{h6}	120 ^{h6}
			Ν	mm	10.5	15		19	32	28	28	-	-
			0	mm	3.5	3.5		4	5	5	5	8	8
			AA	ø mm	5.5	6.3		8.4	10.3	12.1	12.1	-	-
			BB	ø mm	M5	M6	5	M8	M12	M14	M14	M14	M14
			CC	mm	130	239	9	272	344	542	542	482	482
Ram													
External ram dimensions			Р	mm	ø 25	ø 40	0	42 x 42	55 x 55	65 x 65	65 x 65	ø 90	ø 90
Ram bore (with bushing)			Q	ø mm	6 ^{H7}	10 ^{H7}	/	2047	20 ^{H7}	20 ^{H/}	20 ^{H7}	20 ^{H7}	20 ^{H7}
			R	mm	18	30		50	50	50	50	50	50
			S		M5	M8	5	M10	M10	M10	M10	M10	M10
Ton working position		1	mm	8	10		20	20	20	20	20	20	
top working position			U	mm	40	50	2	60	60	60	60	6/	114
I op ram position			V	mm	19.5	27.8	5	38.1	44.6	55	55	6/	114
for pin bore			VV	mm 2)		22		32	40	40	40	40	40
			X	mm		22		32	40	40	40	40	40
			Y 7	01 manar		IVI5				1VI8 0H7	IVIO	IVIO 0H7	IVI8
			7	mm ه		5'''		D	o	ō	0	0'''	0

 $^{1)}$ ±0.01 $^{2)}$ ±0.02

SCHMIDT[®] ServoPress/TorquePress Superior Control Functionality

Attaching a ball screw to a servo or torque motor isn't enough to produce perfect assemblies. Key to consistent pressing results is having a control that communicates in a fast and accurate manner with the motor's drive.

ServoPress module signal amplifier (digitalization preprocessing) converter

SCHMIDT[®] ServoPress and TorquePress modules with Press-Control 700 or 7000 provide:

- True closed-loop force & position control
- Rapid approach of target force or position with no over-shoot, even during dwell times.
- Positioning repeatability of 1 micron under constant conditions
- Adjustable control parameters
- Standard operation profiles for pressing to position, force, delta stroke, slope or external signal with no special programming required
- Pre-set and optimized acceleration/deceleration values
- Graphic display of Force/Time and Stroke/Time facilitates cycle time optimization

Digitalized force/stroke signals PressControl 7000 RT

and TorquePress systems provide.

PressControl 7000 HMI

PressControl 700

To achieve this, the drive, measuring unit and controller must be

fully integrated. This is exactly what the SCHMIDT® ServoPress

Key characteristics:

- Integrated measurement technology (200Hz measuring) frequency)
- Backlash-free stroke measurement
- Zero side load force measurement
- Digitalization of process signals right at the module, making the system impervious to EMI.
- Complete closed loop control system via the SCHMDT[®] PressControl 700 / 7000
- Optimized PLC for press control
- Software based PLC with integrated CNC for rapid signal processing

SCHMIDT® TorquePress Compact, with high efficiency and hollow shaft motor

In addition to the ServoPress series, the **SCHMIDT**[®] **TorquePress** has a number of special features. Among other things, a hollow-shaft torque motor is used, which enables very high press forces with a very high motor torque without additional mechanical transmissions.

Compared to other electric presses, the noise level remains remarkably low under all load conditions. The spindle nut, which is driven directly without the use of additional gears, enables very high levels of efficiency. Thanks to the hollow shaft motor, the **TorquePress** is particularly compact and enables short overall lengths.

SCHMIDT[®] **TorquePress** are EC type-tested in connection with the safety technology options **SmartGate**, **SmartGuard** and **light curtain** and optionally with the particularly economical one **2-hand operation**.

SCHMIDT.

Nominal force of module available

- 100 % of the time
- At any ram position
- For any duration
- Maximum force available in S3 Mode

Direct ram stroke measuring system

Precision sensor and scale integrated into the press module for direct ram stroke measurement. Tied directly to the PLC/CNC of the system for positioning based on ram location.

- Micron level positioning repeatability thanks to high resolution
- Compression compensation under full load
- Correction of ball bearing pitch inaccuracies
- Temperature related material expansions/contractions do not impact measuring results
- High resolution position feedback for process monitoring

Integrated load cell

Load cell tied into the control of the system to provide:

- True closed loop force control of the ram movement.
- No overshoot of the programmed force
- A constant force regardless of part / environment / system changes.
- True force feedback for process monitoring

System Protection

- Automatic spindle lubrication system
- Overload protection clutch
- Active cooling and thermal monitoring of electronic and mechanical components
- Current limiter

Maintenance friendly

- Automatic spindle lubrication system
- Integrated used grease depot
- No filters
- Plug-and-play module recognition

Efficiency

TorquePress 560 is equipped with brake energy recuperation technology.

What does this mean for you?

- Highest degree of efficiency
- Maximum operational availability
- Highest reliability

TorquePress 520

TorquePress 560

SCHMIDT® TorquePress With force outputs from of 20 kN to 100 kN

Press type		TorquePress 520	TorquePress 560
Force F max. S3 25%, 20 s	kN	20	100
Force F 100 % continuous run	kN	10	50
Ram stroke	mm	250	300
Resolution position control	μm	< 1	< 1
Ram speed	mm/s	0 - 260	0 - 200
Resolution PDA force	N/inc	6.25	30
Resolution PDA stroke	μm	4	4.6
Overload protection		electrical	mechanical
Drive		ball screw	planetary roller screw
Weight appr.	kg	95	230
Tool weight max.	kg	25	100
Power supply (50 – 60Hz)	V AC	400 – 480, 3~ / 16 A	400 – 480 V 3~ / 32 A
Dimension H / W / D	mm	1132 / 163 / 315	1438 / 304 / 255
Ram bore	mm	ø 20 ^{H7}	ø 20 ^{H7}
Ram dimension	mm	Ø 50 ^{H6}	ø 60 ^{н6}

Overall dimensions with frame			TorquePress 520	TorquePress 560			
Throat depth	С	mm	160	160			
Table bore	D	mm	ø 40 ^{H7}	ø 40 ^{H7}			
Working height	F	mm	340	420			
Table height	K	mm	132	180			
Table size	ВхТ	mm	300 x 230	370 x 230			
Frame depth	SL 6	mm	530	620			
Frame height	SH 1	mm	670	880			
Total height	SH 2	mm	1662	2098			
Weight approx.		kg	222	584			
Frame							
	А	mm	1154.5	1467.5			
	В	mm	567.5	621			
	С	mm	132	183			
	D	mm	300	370			
	E	mm	510	633			
	SH1	mm	670	880			
	SH2	mm	1662	2098			
	SL6	mm	530	620			
	F	mm	340	420			
Flange							
	G	mm	30	39			
	Н	mm	160	215			
	J	mm	140 ±0.1	194 ±0.1			
	K	mm	78 ±0.1	150 ±0.1			
	Μ	ø mm	100 ^{h7}	80 ^{h7}			
	0	mm	6	6			
	AA		M10	M14			
Ram							
	Р	ø mm	50 ^{H6}	60 ^{H6}			
	Q	ø mm	20 ^{H7}	20 ^{H7}			
	R	mm	50	50			
	S		M10	M10			
	Т	mm	20	20			
	U	mm	60	60			
	V	mm	SW41	-			
	W	mm	15	15			
	Х	mm	6.04 ±0.01	8.04 ±0.01			
	Y	mm	7.8	10.3			

Detailed dimensional drawings can be downloaded: www.schmidttechnology.de

Dynamic Bend Up Compensation Patented Feature

In order to achieve assembly requirements in the 1/100 mm range, compensation of the system yield is required. Work piece, tooling and machine are elastically deformed by the varying forces induced during the pressing process. Once the operation is complete and the press force is removed, this deformation disappears. The result is that the assemblies are not joined to their programmed dimensions. This yielding effect makes it impossible to produce high precision joints regardless of a systems positioning accuracy.

First, a complete process representation of the force characteristic in loaded and unloaded state is necessary so that the system can carry out the required compensation.

Conventional procedures end in the block position – but the process is not finished yet. The system is under force.

In typical applications, the force required to complete an assembly varies up to 40 % from part to part. When freely positioning, such as without a positive stop, the press ram extends to the same target position, regardless of load. But a closer inspection of the completed assembly and the force/distance curve generated, shows that the final pressed position will vary due to the

- The SCHMIDT[®] ServoPress/TorquePress system determines easily and precisely the system elasticity and compensates it dynamically in real time
- Only with dynamic bend up compensation, the end position can be reached to an accuracy of the 1/100 mm range
- Free positioning with compensation of the system elasticity is more accurate than pressing on effect tool stop
- Dynamic bend up compensation does not reduce the process speed
- Dynamic bend up compensation in connection with other intelligent functions, such as offset of tolerance data, has been patented

Example: Press in a Pin in a Bushing

The elasticity of an assembly depends on the equipment, process and the component geometries. This effect becomes significant for assemblies with which the assembly forces of the individual components differ strongly from one another. This can particularly be seen in the example shown. forces in the operation. (figure 1) In order to overcome this effect, **SCHMIDT® ServoPress/TorquePress** systems compensate dynamically to the changing forces. This compensation allows for the assembly to be pressed to the target position, regardless of force (figure 2)

" Δ S" changes proportionally to the force output, that means, the components have different dimensions depending on the force requirement of each component

SCHMIDT® PressControl Machine control units

SCHMIDT® PressControl 75, 700 and 7000 are the latest generation of controls, which allow the design of modern production processes – from the single workstation to complete automation. You benefit from our knowledge in:

- Safety technology EC type approved machines
- Process measurement technology simultaneously measuring while processing
- Process documentation

The control systems have the following features:

- Efficient due to intuitive user interfaces on touch / multi-touch screen
- Fast and safe setup of processes in an easy-to-read window, simple parameterization for manual ram movement and transfer of the actual parameters force and path to the motion blocks (teach-in) for the PressControl 700 and 7000 controls in combination with ServoPress/TorquePress/ElectricPress
- The integrated PLC allows the control of additional inputs/ outputs or sensors/actuators and thus the application-specific set-up of the workstation or system
- The integrated measurement data acquisition is insensitive to interferences (EMC). This results in a high measurement reliability of the entire system
- With the integrated safety technology, the entire system becomes an EC type-approved single workstation
- Service functions enable simple and efficient maintenance
- Guarantee of complete process documentation with clearly traceable component assignment

SCHMIDT[®] PressControl 75

SCHMIDT[®] PressControl 700

SCHMIDT[®] PressControl 7000 RT

SCHMIDT[®] PressControl 7000 HMI

SCHMIDT[®] PressControl 75 Compact functionality

Highly compact yet multifunctional **SCHMIDT®** PressControl 75 available for these press systems:

- SCHMIDT[®] ElectricPress
- SCHMIDT[®] PneumaticPress
- SCHMIDT[®] HydroPneumaticPress

It's easy and intuitive touchscreen allows for quick and efficient process set-up or change-over. Process specific data can be stored in up to 24 datasets.

The **SCHMIDT**[®] **SafetyModule** allows the design of single workstations with safety technology that meets the latest global standards for two-hand cycle initiation, guarding or light-curtain protection.

>>press parameter<<
presstime endposition 0,5 s
>>counter<<
preselect counter off
preselect quantity 10 pcs

Technical Data

Supply voltage	24 V DC					
Current	< 3 A					
Operating temperature	0 – 40 °C					
Protection class	IP 54					
Interfaces	CANopen for PRC - Gateway or					
	CANopen Compact Box IP 2401					
Electrical connections	All connections are pluggable					
Display	2.8" touch screen					
	Process information					
Operation	4 function keys					
	3 languages, switchable					
Modes of operation	Two-hand release with SafetyModule					
	Light curtain with SafetyModule					
	Start button for operation without SafetyModule					
	Workpiece control					
	 Activation of sliding table 					
	Return stroke initation with external signal					
	Blow-out/blow-off					
Operating functions	Piece- or preselection counter					
	Set-up mode					
	BDC dwell time					
	User Management					
Dimensions	90x120x60 (hxwxd)					
Mounting	Fastening screws, optional magnet holder					

Data input

Data output

Data output

SCHMIDT[®] PressControl 700

"All in one" control and visualization for the single workstation

The **SCHMIDT**[®] **PressControl 700** for single workstations is used for the control and monitoring of pressing and joining processes. In addition to precise assembly tasks, the fast acquisition of extensive process data and bidirectional data exchange is becoming more and more important.

The **SCHMIDT**[®] **PressControl 700** real-time controller communicates with the process components via the high-performance and fast field bus EtherCAT with a transmission rate of 100 Mbit/s and a transmission speed of 0.5 ms. With this the press control meets the requirements for fast processing of large data volumes. The leap into other fieldbus worlds is realized by using optional fieldbus gateways.

Process visualization takes place directly on the PressControl 700. Via the Ethernet interface, the control communicates with MES systems and external PCs as well as PRC DataBase and PRC FileX-change software.

The press control system is optimally designed for **SCHMIDT**[®] **press systems**. Thanks to the integrated PLC, process visualization, the best possible compatibility and performance is achieved. All components are tested and matched to each other in the network and are therefore ready for immediate use.

User Surface

- 10.1" Full HD multi-touch-screen
- setup and setting of parameters via "drag & drop"
- compact display of the entire process in the home view
- individual sizing of the process windows (splitter function)
- Ianguage switchable

0	s: 80,00 mm F: 0,00 kN									Fr Feb 09:5	4 202		
					1	move to TD	C positio	n / start press	ing process				
status stoke take release control on release control on release process step process step process step process step process step process step o safety error operating i automatic setup mode conce;cicle a this-cycle a trigger mod to-cycle a trigger mod	DataXc over s cycle 0 info mode cteation cteation e e e ease		PDA shart press cycle PDA active process dials active curve data active calculation active timeout ECC eve sloppe	ns 30 a 0 a 0 a 0 a 0 a 0 a 0 a 0 a	data tra	. mainte	ST Ser	(60) 2020 571 571 571	= 2151 (Decay Trans = 2130 (Decay Trans 4 Do << 22005 //				//
NC Error		٥						6.00	132.00	133	00 Stroke (mm)		134.00
			Sys	tem datase	t		^`	C	operating prof	le	_	Bas	ic se
0	00 Syste	m Da	itaset						ILC position		PDA		
			D	ashboard			^		T		PDA start	1	moti
• 0	02 Electr	onics	3					`,↓	+	•	PDA stop	1	TOC
								2 1	-	7	increment PDA stroke	1	
0.0	U4 Speed	ome	ter					F 100 N	<u>s</u>		increment PDA force	1	
0	05 Rev N	leter						3		6	cyclic taring force sensor	1	ined
0	11 snap i	īt						80,00 mm 800 N			process lin	nits	
			Dri	ve Profiles			^	•		9	position	0	
				-							maximum		

Technical Data	
Industrial PC	Intel E3990 processor 2 GB main memory 16 GB on-board Flash (eMMC) 4 GB CFAST Linux operating system
Interfaces	2 x USB 2.0 2 x USB 3.0 1 x Ethernet, M12 (LAN1) 1 x Ethernet, M12 (LAN2) 1 x EtherCAT-P, M8
Power supply	24 V DC (EtherCAT-P)
Current consumption	max. 1,3 A
Weight	ca. 1,9 kg
Ambient Temperature	0 °C +40 °C
Humidity	0 90 % relative humidity (not condensing))
IP Rating	IP 54

SCHMIDT® PressControl 7000 Compact system control for intelligent process control

The **SCHMIDT**[®] **PressControl 7000 RT** for single workstations is used for the control and monitoring of pressing and joining processes. In addition to precise assembly tasks, the fast acquisition of extensive process data and bidirectional data exchange is becoming more and more important.

The **SCHMIDT**[®] **PressControl 7000 RT** real-time controller communicates with the process components via the high-performance and fast field bus EtherCAT with a transmission rate of 100 Mbit/s and a transmission speed of 0.5 ms. With this the press control meets the requirements for fast processing of large data volumes. The leap into other fieldbus worlds is realized by using optional fieldbus gateways. Process visualization takes place directly on the PressControl 700. Via the Ethernet interface, the control communicates with MES systems and external PCs as well as **PRC DataBase** and **PRC FileXchange** software.

The press control system is optimally designed for **SCHMIDT**[®] **press systems**. Thanks to the integrated PLC, process visualization, the best possible compatibility and performance is achieved. All components are tested and matched to each other in the network and are therefore ready for immediate use.

SCHMIDT[®] PressControl 7000 HMI

- 21.5" Full HD multi-touch screen
- Multi-axis applications can be visualized
- Setup and setting of parameters via "drag & drop
- Installation of optional software tools such as SCHMIDT[®] PRC DataBase or PRC FileXchange is prepared

Technical D Industrial PC

Interfaces

Power suppl Current cons Weight Ambient ten Storage tem Humidity IP Rating

4 (3800m)	El annum B success	monstart an market and the second
		token

ata PressControl 7000 RT			Technical Data PressC
	Intel E3990 Processor 2 GB main memory 16 GB on-board flash (eMMC) 4 GB CFAST Linux operating system		Industrial PC
	 x display port x USB 2.0 x USB 3.0 x Ethernet, RJ45 (LAN1 via integrated switch on 3 ports) x Ethernet, RJ45 (LAN2) x EtherCAT, RJ45 Universal Fieldbus, integrated compartment for installation 		Interfaces Power supply Current consumption
1	24 V DC (via 3-pin plug)		Weight
umption	1 A		Ambient temperature
	approx. 0.73 kg		Storage temperature
perature	0 °C +65 °C		Humidity
perature	-20 °C +70 °C		IP Rating
	0 90 % relative humidity (not condensing)		Assembly
	IP 20; PressControl 7000 RT placed in electrical cabinet		

Technical Data PressControl 7000 HMI				
Industrial PC	Intel i5-7xxx Processor 64 GB CFAST operating system 512 GB HDD data memory Operating system Windows 10			
Monitor	21.5" full HD monitor (1920 x 1080) with capacitive multi-touchscreen			
Interfaces	1 x HDMI 2 x USB 2.0 2 x GBit Ethernet, M12, X-coded (LAN1, LAN2) 2 x integrated loudspeaker			
Power supply	24 V DC (via 4-pin M12 plug, T-coded)			
Current consumption	2 A			
Weight	approx. 9.5 kg			
Ambient temperature	0 °C +40 °C			
Storage temperature	-20 °C +60 °C			
Humidity	5 90 % relative humidity (not condensing)			
IP Rating	IP 54			
Assembly	VESA 75			

User surface for professional assembly For PressControl 700 and 7000

The user interface for professional assembly is installed in the **SCHMIDT**[®] **PressControl 700** and **7000**. The functionality has been developed specially for assembly operations with immediate reaction in the process.

The following functions are available

- process visualization
- process data management
- development tool (PLC editor)
- SCHMIDT[®] PRC DataBase, PRC FileXchange, PRC OPC optional

Process Monitoring

- high graphical curve resolution for detailed view of curve segments
- three graphic displays; force/stroke, force/time and stroke/time for process analysis and optimization
- extensive tool library
- result visualization OK/NOK (green/red)
- tolerance observers

Process Output

Actual system statuses are displayed both text-oriented and graphically and thus enable a transparent process overview for quick analysis and troubleshooting.

Software Options

The comprehensive software packages for process data management and process optimization can be activated individually and specifically stored in data sets.

Characteristics

- easy and fast setting of parameters for the processes
- definition of data sets and motion profiles by parameter setting
- process optimization by switching the process display (F/s, F/t, s/t)
- easy definition and evaluation of processes via quality observers
- 12 QA observers can be defined as F/s windows or stroke tolerances as required
- safe detection of bad parts (NOK)
- Clear documentation and part assignment
- software PLC to freely program sequences
- service functions for diagnosis and system updates

User Interface SCHMIDT® PressControl 700

1 + 2 All tolerances can also be used inverted (blocking ranges) 3 Stroke tolerances can be adapted to curve gradient

SCHMIDT® ServoPress/TorquePress Driving profiles and applications

SCHMIDT[®] **ServoPress** / **TorquePress** enable simple configuration of the driving profiles with motion blocks. In order to realize a quick setup, different standard driving profiles are available.

Positioning to "stroke" Normal driving profile, typically combined with bending compensation. **Closed loop "force" control** For processes in which the force achieved is a measure of the process quality, e.g. material compressing processes.

Driving on touch force and "delta stroke".

combined as desired.

For processes in which component tolerances must be detected. The press scans the surface and presses in to a specific differential dimension as soon as the defined force is reached. Driving on "Force increase" The return stroke is initiated at a defined force increase (slope)

Plugging blind bores – a sphere is pressed in and crimped. Force output correlates to material displacement to determine density and retain force independent of stroke or the safe seating of bearings on shafts

Pressing to a functional dimension with force-controlled touching of the body edge and subsequent relative movement (delta stroke)

Pressing in expanders or crimping cable shoes. The sealing or holding function depends on the correlation of force and displacement.

n to a nension force is

Experience shows that these standard driving profiles and com-

binations cover most applications. Up to 8 motion blocks can be

Visualization and process analysis for PressControl 700 and 7000

Visualization user surface

Important parameters for assessing the quality of press fits are the press force and the press stroke. The data of these measured variables are recorded during the process and displayed by the software as a force-displacement curve F/s or F/t or s/t.

For quality assurance of the joining process, freely definable tolerances are provided in the form of force-stroke windows and stroke tolerances. With the help of these criteria, the qualitycritical areas can be precisely monitored. If the tolerances are not adhered to in the monitored curve areas, appropriate applicationspecific reactions can take place (e.g. selection measures). Tolerance criteria can be created very easily and progression curves can be displayed exactly. Not only the working stroke but also the return stroke are important for the evaluation of the curves. The high resolution of our measuring systems allows a large number of measuring points, which are necessary for a process-reliable evaluation. Integrated zoom and measurement functions allow detailed statements on the joining processes.

Process analysis - graphic display force over stroke

SCHMIDT[®] MoveTol Patented offset of tolerance, data software for **PressControl 700** and **7000**

Assembly parts are subject to certain manufacturing tolerances. Height deviations of the parts result in an offset of the curves in the curve window. The curves of the parts with larger tolerance deviations can then lie outside the created tolerance limits and are declared as bad parts.

The height tolerances of the parts can be taken into account with the "Tolerance data offset" function. The defined tolerance windows and stroke tolerances are shifted by the distance to a reference position. The good/bad evaluation is then performed.

Offset of the tolerance data is relative to freely selectable references.

SCHMIDT[®] **Software-Tools** Interface for data evaluation and control

To cover the versatile requirements in the field of data management, **SCHMIDT Technology** offers modular software tools. It includes possibilities in the area of machine control, data storage and exchange as well as visualization and analysis. This enables versatile requirements of quality assurance, traceability and optimization of production processes can be realized. A large number of up-to-date interfaces are available at Fieldbus level and allow the press system to be easily integrated into higher-level systems. The data obtained during the pressing process allows conclusions to be drawn about quality fluctuations in components or even preliminary processes in production. Therefore, not only data acquisition and storage, but also analysis and evaluation play a central role. **SCHMIDT® PRC DataBase** and **PRC FileXchange** offer a wide range of options for this purpose. An evaluation can be carried out either with on-board tools or by user IT systems to which the process results are transferred.

Ethernet Fieldbus

SCHMIDT[®] PRC DataBase Database software for PressControl 700 and 7000

SCHMIDT[®] **PRC DataBase** is an optional software for the modular control system **SCHMIDT**[®] **PressControl 7000** or **SCHMIDT**[®] **PressControl 700**. The database software is used for storing and analysing the data of the control system – process specifications and process results – particularly under quality assurance aspects.

Characteristics

- Documentation
- Analysis
- Quality assurance
- Traceability
- Data export in CSV format
- Q-DAS interface with certification

SCHMIDT® PRC FileXchange Safe exchange of process data

In addition to data exchange within an automation solution via Fieldbus, data exchange can also be performed via data files. For every press process all relevant process results, tolerances, observer, and parameters are written into a file whose format and content can be configured via an intuitive user interface.

- The following output formats are available:
- Microsoft Excel (CSV)
- Q-DAS
- SCHMIDT® CRV/TOL
- XML

The transmission of production data is synchronized from Press-Control to PC (File System). That means if the connection between PressControl and PC is interrupted the process is stopped, the event is recorded. Once the connection is re-established the data of the last press process will be transmitted again.

It is also possible to import default values for press processes from a configuration file. A production range which comprises several different products can, for example, be managed via standard PC application and thus be used as production database.

The respective product-specific configuration file can be created by the **SCHMIDT® PressControl HMI** for all relevant process parameters and transferred to the customer's management software via xml file.

export

visualization example

Create configuration file		8. 	Import properties
Target directory C1PRCFX_Setup_V1_0_0_24	Manage configur	ment of product Automatic im Source	Manual import directory CFX_Setup_V1_0_0_24/vm-sp405-rt.
File name Product A		File na Produ	metC
Description Pressing in bush Elerance windows A-01, A-105 Stroke tolerance A-554	Transfer eters via	of process param- xml-file	otion
Control name		Control	name 005-rt

Generating configuration files (Parameters for particular joining processes) Automatic or manual import into the press control

user


SCHMIDT[®] **PRC DataXchange** Bi-directional data exchange with higher-level controls

The **PRC DataXchange** interface is available for communication between a **SCHMIDT**[®] **press system** and a higher-level control system.



DataXchange Input

Parameter-Transfer to PressControl Dynamic adaptation of processes

- Control type (force, stroke, ext. signal, relative position, ...)
- Position
- Speed
- Force
- Motion block change (stopping, flying, ext. trigger signal)
- Dwell time

DataXchange Output

Data-Transfer to Master PLC

for connection to MES and ERP systems

- Reached position
- Reached force
- Actual values position and force
- Curve results
- Tolerance values
- Status signals of the system
- Error statesPress axis information

SCHMIDT® PRC OpenFieldBus

OpenFieldBus allows a completely custom specification and programming of driving profiles and sequences by a master control as well as the bidirectional transmission of all relevant data. To implement individual requirements in the press process, the complete command set can be accessed. At the same time, the advantages of the integrated force-stroke monitoring and control of the press system with all evaluation functions can be utilized

Characteristics

- Access to the entire command set of the SCHMIDT[®] press control
- Transmission of process results to the master controller
- Individual definition of joining processes, driving sets and data exchange



Master-PLC

Data exchange via SCHMIDT® PRC OPC UA

OPC UA represents a universal and manufacturer-independent possibility for data transmission used for industrial applications.

The OPC server retrieves relevant process data via Ethernet based on the communication protocol of the **SCHMIDT® PressControl** and makes it available as OPC objects. The OPC client can use all the relevant data items provided by the server and use it for analysis or control according to customer requirements.



SCHMIDT[®] Hardware-Tools Proven components for system integration

SCHMIDT® PressControl 700 and 7000 communicate with higher-level control systems via a standardized interface program. All relevant system states as well as bad part detection performed by simple signal exchange from one control to the other.



SCHMIDT® PRC Gateway

- EtherCAT-connections to PressControl (Master) und PDA (Slave), with 24 V-power supply via EtherCAT-P
- 24 V-Interface with 16 inputs and 16 outputs (up to 0.5 A / output)
- short circuit proof and overload protected
- status-LEDs for EtherCAT-Bus and In- / outputs
- encoder-interface
- interface for external hand wheel as handheld
- top-hat rail mounting



Communication via fieldbus-systems

All common physical interfaces can be used for signal exchange with the automation environment.

- interchangeable modules UniversalFieldBus (UFB)
- further fieldbus interfaces via external gateway
- USB



External handwheel as handheld

for SCHMIDT[®] PressControl 700 and 7000 RT in combination with SCHMIDT[®] ElectricPress with process monitoring or SCHMIDT[®] ServoPress/TorquePress, connection via SCHMIDT[®] PRC Gateway



EtherCAT-P Compact Box

- 8 digital channels, usable as inputs or outputs
- signal connection by screwing via M8 plug connector
- power supply (24 V) via EtherCAT-P
- Ioad currents of the outputs up to 0.5 A
- total current of all outputs 3 A



SCHMIDT[®] PressControl

System architecture

SCHMIDT® PressControl does work as a system control and takes over the process monitoring. The hard- and software components forming a system concept with real time characteristics. This is guaranteed by a system architecture with CANopen fieldbus. Press force monitored **SCHMIDT®** ManualPress,

SCHMIDT[®] (Hydro-)PneumaticPress, SCHMIDT[®] ElectricPress or SCHMIDT[®] ServoPress/TorquePress will be activated via fieldbus. The collected measuring data as well as in-/output data will be exchanged by the fieldbus.

SCHMIDT[®] PressControl 700

system architecture



SCHMIDT® PressControl 7000 RT with 7000 HMI or 700 HMI



SCHMIDT[®] Single Workstations Ergonomics with certified safety technology

SCHMIDT® workstations are supplied ready to use with certified safety technology and corresponding operating elements. Depending on customer requirements, workstations can be equipped with the following safety elements:

- SCHMIDT[®] SmartGuard protection cover
- **SCHMIDT®** SmartGate protective housing with automatic doors
- light curtain
- two-hand safety

The delivery includes:

- Module SCHMIDT[®] presses mounted on stand or pedestal
- SCHMIDT[®] PressControl 75 (in two-hand release and light curtain versions), 700 or PressControl 7000 with pendant arm system
- Press base PU 20 / PU 40 in rigid or height-adjustable design, depending on the safety concept optional or as standard

All systems are EC type-approved!









SCHMIDT[®] SmartGate Shorter process cycles and increased safety standards

SmartGate is a protective enclosure with automatic doors. The access to the process area is via two transparent, horizontally guided door elements. Key benefits of SmartGate over other safety concepts, such as light curtain or two-hand systems, are the significant increase in ergonomics and workflow efficiency through reduction of required safety margins and the excellent accessibility of the process space.

SmartGate sets new standards in the field of safety by completely closing off the process area, completely eliminating unintentional third-party intervention or fragmentation. SmartGate is particularly suitable for processes with the risk of splintering due to protection against flying parts or spalling.

When designing SmartGate, we ensured that all surfaces are as easy to clean as possible and that there are no areas where residues or particles can accumulate. High demands on purity and cleanliness, as they occur, for example, in applications in medical technology can therefore be easily met.

SmartGate				
Max. opening width	720	mm		
Variable speed	50 – 350	mm/s		
Typical opening time	2.2 s			
Typical closing time	1.8 s			
Noise emission	< 60	dB(A)		
Cell size 1	1010 x 883	mm		
Cell size 2	1010 x 1049	mm		
Protective door	laminated safety glas	laminated safety glass (VSG)		
Safety category	Plexiglass			



- Protection of the working area from unintentional intervention
- Splinter protection from chipping of parts
- Optimization of the safety distances to the complete danger
- Consideration of quality assurance requirements (NIO
- Cycle time and process optimization through programmable opening and closing speed (<2 s)
- Very high energy efficiency due to linear motor drive

SCHMIDT® Safety Technology Smart Safety Concept for Servo and Torque presses

The transparent protective housing entirely encloses the working area during the press process. It thus prevents the user and a third person from getting their hands into the danger area and efficiently protects against the particles or splinters that may be ejected. The distances to the working zone are minimized which considerably improves the ergonomics and the efficiency of the workstations. The high dynamics of the protective housing with numerical control and its variable positioning capability and traversing velocity optimize the process cycle. The smart construction prevents any trap points in the enclosure.

SCHMIDT[®] **SmartGuard** is a protective shield for **TorquePress 520**, **TorquePress 560** and **ServoPress 605** to **620**.

Servopress 617

SCHMIDT

SmartGuard	type	SP 605	SP 616	SP 617	SP 620	TP 520
Variable opening stroke	mm	280	350	410	500	390
Speed opening	mm/s		200 - 1000			
Speed closing	mm/s	200 - 500				
Drive	type		linear motor			
Deep	mm	434	485	573	644	599
Wide	mm	232	286	312	359	343
Height	mm	1018	1111	1440	1840	1640
Material guard	PC	antistatic / transparent				
Electr. safety lock		Ple				



Characteristics

- Protection of the working area from unintentional intervention
- Splinter protection from chipping of parts
- Visible working space
- Optimization of the safety distances to the complete danger area
- Consideration of quality assurance requirements (NIO consideration)
- Cycle time and process optimization through programmable opening and closing speed (<2 s) and the opening height
- Very high energy efficiency due to linear motor drive
- Type approved
- ESD version possible





Classic Safety Concepts

Light curtain with guarding

The light curtain control provides optimum safety to the user. The process area is protected with polycarbonate windows against contact. A light curtain protects the access to the hazard area on the side of insertion. The working process is immediately interrupted and the dangerous motion of the press is stopped. The cycle can be continued automatically after leaving the danger area. In combination with **SCHMIDT® ServoPress**, the light curtain control is the basic version. The press can be activated via the light curtain. Depending on the application, it can be selected between 1-cycle and 2-cycle activation.

Two-hand safety technology

In basic design, SCHMIDT[®] PneumaticPress, SCHMIDT[®] Hydro-PneumaticPress as well as SCHMIDT[®] ElectricPress are operated with two-hand safety technology. The user must keep both switches in the activated position. If one switch is released ahead of time, the press stroke is interrupted. This applies to all positions above the automatic stroke takeover that is started from the point where the dangerous closing movement is finished. From the stroke takeover, the stroke is continued automatically.



SCHMIDT® Press Bases Ergonomic in focus

SCHMIDT[®] **Press Base PU 20** and **PU 40** for a safe and vibrationproof installation of all **SCHMIDT**[®] **Press Systems**.

Both press bases are available in two versions:

- Fixed columns with height adjustable in 10 mm (0.4") increments from 780 to 1080 mm (30.7" 42.5")
- Infinitely variable motorized height adjustment from 725 to 1075 mm (28.5" – 42.3")



PU 20 with two variable columns



PU 40 with four fixed columns

Technical Data			PU 20 (2 columns)	PU 40 (4 columns)
Fixed columns	Н	individually	780 – 1200 mm	780 – 1200 mm
Motorized variable columns	z	stepless	725 – 1075 mm	725 – 1075 mm
Lifting capacity		kg	600	1200
Width x depth			on request	on request
Foot rest			-	✓

PU 40 with four variable columns

 $^{\scriptscriptstyle 1)}$ Height ${\bf H}$ measured from floor space to press table top

²⁾ Fixing dimension Z stand on PU20, resulting height of the press table depends on frame type (see dimension K in the respective press chapters). Example: frame type 3 for press No. 25 K = 60 mm, PU20 (725 mm to 1075 mm) and press table height 60 mm results in total press table infinitely adjustable from 785 mm to 1135 mm

SCHMIDT[®] Four-column Gantry

SCHMIDT[®] Four-column gantries used in manual workstations, and automated assembly lines, are suitable for all SCHMIDT[®] Presses with extraordinary requirements in all working area.

In order to consider the large number of applications and cases, the design is adapted specifically to your requirements. All individual requirements can be taken into account. Short delivery times are realized because of in-house production. Contact us with dimensions (see table), and we can supply you with a proposal.

Characteristics base plate

- Coated: RAL 7035 (light-grey)
- Cross T-slot 45° 14^{H7}
- Central bore 40^{H7}, other bores on request

Characteristics cover plate

- Coated: RAL 7035 (light-grey)
- Connection drill pattern for the required press
- Chromium-plated columns





SCHMIDT[®] Slide Tables For efficient production

SCHMIDT[®] **Slide Tables** are specially designed for the high forces of press systems and where a position requires high precision against an adjustable stop. It is an economic solution for tall parts and for placement of parts outside of the danger area. They can be mounted, depending on the type, both in longitudinal and lateral positions, and can be adapted for automated processes.

Characteristics

- Force closure due to unique anvil system
- Backlash-free guide systems for consistent smooth running over the entire stroke
- Operator safety due to covering of danger points (no pinch points)
- High reliability due to protection against particle ingress
- Dynamic end-position cushioning prevents hard impacts
- Triggering of the press stroke via adjustable position sensors



ST 100M / ST 100P



ST 150M / ST 150P



Туре		ST 100M	ST 100P	ST 150M	ST 150P
Pressure load	kN	100	100	150	150
Max. stroke V1 Max. stroke V2	mm	79 159	80 160	129 199	130 200
Repeatability working position	mm	±0.01	±0.01	±0.01	±0.01
Repeatability loading position	mm	±0,2	±0,01	±0,2	±0,01
Dimensions B/H/T V1 Dimensions B/H/T V2	mm	142 / 39 / 220 142 / 39 / 300	188 / 39 / 211 188 / 39 / 291	159 / 55 / 301 212 / 55 / 271	159 / 55 / 279 212 / 55 / 349
Weight V1 Weight V2	kg	3.6 6.9	4.2 7.6	10.8 11.8	12.7 14.1
Max. tool weight	kg	10	10	10	10
Operating mode		manual	pneumatic	manual	pneumatic

SCHMIDT[®] Slide Table ST 100M longitudinal with handle



SCHMIDT[®] Slide Table ST 100M cross mounting with adapter plate for fastening on the fixture mounting plat



SCHMIDT® Customer-Specific Solutions

Standard 'out of the catalog' products, customized or complete turn key solutions. **SCHMIDT Technology** is an invaluable source for your assembly needs, with the center point being a press. We welcome the opportunity to evaluate your application, perform feasibility studies, process sample parts to determine process capability from a control, as well as monitoring standpoint.

We can take your applications from process development and manufacturing of prototype tooling to provide you with custom designed, turn-key solutions.

SCHMIDT[®] engineers and sales force have gained a wealth of experience while working on a wide array of applications.

SCHMIDT Technology products are suitable for a broad variety of industries and can be tailored to the specific requirements and challenges that applications present, from very basic and simple pressing operations to intelligent, precise and complex processes, combined with monitoring.

The ever rising need to log and exchange process data with third party systems can easily be addressed by the various ways our control systems can be interfaced.

Your need is our challenge. We look forward to the opportunity to be of service.





SCHMIDT® ElectricPress 43/343 Automation

Integrates easily and quickly into an automated system; ideal for new design concepts, integration or as a replacement in an existing production line.



SCHMIDT® Customer-Specific Solutions



"Compliant Pin" application

SCHMIDT[®] **ServoPress Systems** are the ideal tool for press-fit applications. Their integrated process data and closed-loop force control is perfect for the assembly and disassembly of electronic components. In contrast to soldering, press-fit contacts on a circuit board requires precisely defined and closely monitored assembly processes at very slow speeds. A **SCHMIDT**[®] **Press** can be the solution.

All **SCHMIDT**[®] **Press Types** can be integrated in a rotary indexing system. Depending on the requirements of the customer, an individual design is planned.

Hybrid Assembly Cell Configuration with

- a monitored PneumaticPress
- a monitored ServoPress
- a conventional HydroPneumaticPress

A single **SCHMIDT**[®] **PressControl 7000 RT** can control all of these presses as well as an indexing table. It acquires all stroke/force process data, which can then be transmitted to the **SCHMIDT**[®] **DataBase** software for storage and analysis.



SCHMIDT[®] **Support** Close to the customer thanks to a perfect service

SCHMIDT® DemoBus

Our press technology will come to your premises. The SCHMIDT® DemoBus contains a selection of fully functional presses and accessories.

- See the innovative news and trends
- Get a wide overview over our products
- Do not lose time and save travel costs
- Discuss your assembly applications with our experts
- Conduct trials (by prior arrangements)



SCHMIDT[®] CompetenceCenter

We have a large number of presses and press systems in our exhibition and testing area at your disposal. Visitors are welcome to our Competence Center to discuss at first hand their specific requirements with our team of experts, who will be pleased to conduct trials on their tools and offer advice and best solutions for all applications.

SCHMIDT® TrainingCenter

Our training packages prepare the participants fully in theory and practice for their daily work with SCHMIDT® Press Systems, by offering comprehensive user training courses and seminars on complex technological products. These training courses deal with the handling of the products as well as the correct use of the control and process software. SCHMIDT Technology stands for high quality products and their efficient use on site.







SCHMIDT[®] Services portfolio We support you either on site and from in-house

In order to meet the high quality standards of modern production, to comply with legal requirements periodic calibrations and safety tests of the press systems according to DIN ISO 9000, safety measures are required.

SCHMIDT Technology assists you by means of a strong service package in meeting these requirements.

SCHMIDT® Calibration

for force-monitored press systems

SCHMIDT® PressControl

- Checking the measurement system
- Calibration
- Issue of a test certificate incl. test report
- Calibration sticker on the machine



Telephone support

Our service is available Monday through Friday from 7:30 am to 4:30 pm (GMT +1). Emergency telephone assistance and a reaction time within 24 hours are our standard.

SCHMIDT® SafetyCheck

for all SCHMIDT® PressSystems with type approval

- Test according to the relevant standards
- Measurement and test of the two-hand switching
- Follow-up measurement
- Functional safety check
- General functional check
- Issue of a test report
- Test sticker on the machine

For Light Curtain Systems

Additional test according to the relevant standards

Service Center world wide

Head Quarter SCHMIDT Technology GmbH

Feldbergstr. 1 · 78112 St. Georgen im Schwarzwald Germany support@schmidttechnology.de · Phone +49 7724 899 300

Service Center US – 24/7 Hotline

SCHMIDT Technology Corp. 280 Executive Drive Cranberry Township, PA 16066 USA service@schmidtpresses.com · Phone +1 (724) 814-5241

Service Center Asia NIXMA TECHNOLOGY CO., LTD.

9/79 Moo 5, Phaholyothin Road, T. Klong Nueng, A. Klong Luang, Pathum Thani 12120 Thailand www.schmidtservicecenter.asia · Phone +66 2902 2394

Service Center UK APS Ltd Unit 21, Easter Park · Benyon Road Reading · Berkshire, RG7 2PQ UK vincent.small@aps-Itd.co.uk · Phone +44 777 358 9201

Service Center Hungary, Bulgaria, Romania Eckerle Industrie Kft.

Dózsa György út 44 · 6200 Kiskörös Hungary info@hu.eckerle-gruppe.com · Phone + 36 (0) 78 / 511 400